



## **Framing Authority**

# **Project Manual**

**With Job Site Forms**

## **Independence Village**

Prepared by:  
Framing Authority  
in association with:  
U.S. Compliance Systems, Inc.

Disclaimer: This Project Manual coincides with selected portions of our safety program located at:

27252 Southfield Rd Suite 4  
Southfield, MI 48076

It is not all inclusive. To the best of our knowledge, the information contained herein is accurate as of the above date. U.S. Compliance Systems, Inc. accepts no responsibility for errors or omissions.

# **Framing Authority**

## **PROJECT MANUAL OVERVIEW**

It is our policy to provide a work environment that is inherently safe -- free from conditions that are unsanitary, hazardous, or dangerous to the health and safety of our personnel and the subcontractors with whom we work. Prior to performing work, job site personnel will be made aware of our safety and health policies as well as appropriate safety standards to prevent accidents and injuries. Accident prevention demands a commitment from all personnel. That commitment includes an awareness of proper work methods, use of personal protective equipment, and proper use of tools and equipment. Competent persons will, on an on-going basis, review work procedures and adherence to safety standards and immediately address areas in which deficiencies are found. Defective tools and equipment will be immediately taken out of service. Only those qualified by training or experience may operate machinery and equipment.

We want all personnel to become actively involved in our safety program. Suggestions for improved safety procedures are welcome. Safety meetings will be held on a regular basis and they will address safety issues appropriate to the work at hand. During these meetings, employees are encouraged to raise any safety related question or concern. On multi-contractor job sites, safety meetings may, depending on the circumstances, focus on the hazards created by other contractors and how those hazards may impact on our personnel.

Project manuals will be kept at individual job sites to enable the supervisors, competent person(s), employees, and subcontractors to have quick reference to major safety requirements of items of equipment or work procedures. This manual is not a complete safety program; our complete detailed safety program is maintained at our main office located at:

27252 Southfield Rd Suite 4  
Southfield, MI 48076

On the job site, safety concerns should be resolved by your supervisor or the competent person.

All personnel are free to, and encouraged to, review appropriate OSHA safety standards maintained in our safety program.

Immediately following this manual are job site forms appropriate for our work.

# Framing Authority PROJECT MANUAL

## INDEX

<u>PAGE</u>	<u>TOPIC</u>
	GENERAL SAFETY POLICIES AND PROCEDURES
1	<u>ACCIDENT/INJURY PREVENTION</u>
1	<u>SAFETY PROGRAM ADMINISTRATOR</u>
2	<u>EMPLOYEE INVOLVEMENT</u>
2	<u>HOUSEKEEPING</u>
3	<u>EMERGENCY ACTION PLAN</u>
3	<u>EMERGENCY MEDICAL RESPONSE</u>
4	<u>FIRE PREVENTION PLAN</u>
4	<u>PORTABLE FIRE EXTINGUISHERS</u>
5	<u>FIRE PROTECTION</u>
6	<u>FIRST AID &amp; FIRST AID KITS</u>
9	<u>SANITATION</u>
10	<u>LIFTING, PUSHING &amp; PULLING</u>
11	<u>SLIPS, TRIPS &amp; FALLS</u>
12	<u>DRUGS AND ALCOHOL</u>
12	<u>SMOKING</u>
12	<u>ACCIDENT INVESTIGATION</u>
13	<u>POSTINGS</u>
14	<u>RECORDKEEPING: INJURIES &amp; ILLNESSES</u>
15	<u>INCIDENCE RATE</u>
15	<u>SAFETY MEETINGS</u>
16	<u>ENFORCEMENT</u>
17	<u>SCHEDULE OF ENFORCEMENT ACTIONS</u>
	JOB SPECIFIC - EQUIPMENT SPECIFIC SAFETY PROCEDURES
1	<u>ABRASIVE WHEELS</u>
2	<u>AERIAL LIFTS</u>
3	<u>COMBUSTIBLE &amp; FLAMMABLE LIQUID HANDLING</u>
4	<u>COMPANY VEHICLES</u>
5	<u>COMPRESSED GAS CYLINDERS</u>
7	<u>CRANES</u>
9	<u>DEMOLITION</u>
10	<u>DISPOSABLE RESPIRATORS</u>
12	<u>ELECTRICAL WORK - WORKPLACE SAFETY</u>
15	<u>EXTENSION CORDS</u>
15	<u>GROUND FAULT CIRCUIT INTERRUPTERS</u>
16	<u>HEAVY EQUIPMENT AND ELECTRICAL POWER LINES</u>
16	<u>HOISTS</u>
17	<u>LIGHTING</u>
17	<u>LP-GAS STORAGE</u>
17	<u>LP-GAS TEMPORARY HEATING</u>
18	<u>MACHINE GUARDING</u>
19	<u>MACHINERY</u>
19	<u>RIGGING FOR MATERIAL HANDLING</u>
20	<u>SCISSOR-LIFT FALL PROTECTION</u>
21	<u>SIGNS &amp; TAGS</u>
22	<u>STAIRS</u>
23	<u>TOOLS: HAND</u>
23	<u>TOOLS: PNEUMATIC POWERED</u>
25	<u>TOOLS: POWDER-ACTUATED</u>

- 26 VENTILATION
- 27 WELDING, CUTTING AND BRAZING
- 31 IDENTIFICATION OF HAZARDOUS JOB SITE MATERIALS

#### OSHA COMPLIANCE PROGRAMS

- 1 CONTROL OF HAZARDOUS ENERGY [OVERVIEW]
- 3 EXPOSURE CONTROL PLAN [OVERVIEW]
- 4 FALL PROTECTION [OVERVIEW]
- 5 FORKLIFTS [OVERVIEW]
- 5 HAZARD COMMUNICATION
- 6 HEARING CONSERVATION [OVERVIEW]
- 6 PERMIT-REQUIRED CONFINED SPACE [OVERVIEW]
- 7 PERSONAL PROTECTIVE EQUIPMENT [OVERVIEW]
- 8 RESPIRATORY PROTECTION [OVERVIEW]
- 8 SCAFFOLDS & LADDERS [OVERVIEW]

#### JOB SITE FORMS

Project Emergency Phone Numbers  
Designation of Competent Person(s)  
Job Site Checklist  
Enforcement Documentation  
Hot Work Permit  
Hand Signals for Cranes  
Forklift Checklist  
Emergency Action Plan & Fire Prevention Plan  
Accident Investigation Form

**NOTE: Job site forms are located at the end of the Project Manual.**

# **GENERAL SAFETY POLICIES AND PROCEDURES**

## **ACCIDENT/INJURY PREVENTION**

Our safety program is designed so that our employees do not work in conditions that are unsanitary, hazardous, or dangerous to their health or safety.

One lax moment in terms of safety may result in a lifetime of needless pain and suffering. Disregarding safety standards may even be fatal. While an accident may happen in an instant, the consequences may last for years.

Accident prevention requires a commitment from all personnel within our company to actively participate in our safety program. All personnel should be aware of job site hazards and follow procedures to eliminate these hazards by proper work methods, use of personal protective equipment, and proper use of tools and equipment. All persons are encouraged to ask questions and make positive suggestions for safety improvement.

Competent persons will be designated to provide job site expertise as well as regular inspections of equipment, materials, and procedures. Competent persons will have the authority to stop work if a safety hazard is identified and it cannot be corrected immediately.

All machinery, tools, materials and equipment deemed unsafe will be taken out of service by physically removing, tagging, or locking controls to render them inoperable.

Only persons qualified by training or experience will be allowed to operate equipment or machinery.

All tools and items of equipment will be used for the purpose for which they were designed. For example, a wrench is not a hammer; a ladder is not a horizontal plank; a fire extinguisher is not a cooler!

Never take chances or attempt any job without being aware of the proper procedures, the potential safety hazards, and the methods to reduce or eliminate risk.

## **SAFETY PROGRAM ADMINISTRATOR**

Our Safety Director will administer this safety program and has overall responsibility for the implementation of this program. The safety director will ensure each employee has appropriate safety training for the tasks to be performed.

Additionally, duties of this position include:

- a. the actual training of personnel.
- b. maintenance of training records.
- c. random inspections to verify adherence to safety rules and policies.
- d. completion of specific tasks identified within our OSHA compliance programs found in Section III of this safety program.

Our Safety Program Administrator is: Florin Maidaniuc

The duties of this position may be delegated to other personnel who are competent persons by virtue of training or experience.

The responsibilities of this position may not be further delegated.

### **EMPLOYEE INVOLVEMENT**

All employees are encouraged to participate actively in our safety & health program. Do not hesitate to point out perceived safety deficiencies to your supervisor or the competent person -- you may prevent an injury to yourself or a fellow worker. With the goal of providing a safer worksite for all of us, employee suggestions for improving safety management are welcomed and encouraged. Never perform any task on which you are not confident in your understanding of the safety procedures. If in doubt, ask your immediate supervisor for guidance.

### **HOUSEKEEPING**

Housekeeping? On a job site? What's that all about? It's about safety! Employees are to maintain a neat and orderly work area *as far as practical*. Housekeeping and general cleanliness have a direct effect on safety and health. Proper housekeeping can prevent slips and falls, allow easy egress in the event of an emergency, prevent falling object injuries, and enhance fire safety. Below listed are general housekeeping rules:

- a. walking/working surfaces shall be kept clean and dry.
- b. do not allow construction debris to accumulate.
- c. stored materials will be neatly stacked at the job site.
- d. containers, when not in use, will be sealed.
- e. no objects will be left unattended on stairways.
- f. entrances and exits will be properly marked and not blocked.
- g. tools shall be properly cleaned and put away after use.

## EMERGENCY ACTION PLAN

An Emergency Action Plan, if appropriate, will be posted at the job sites along with emergency telephone numbers and an escape route diagram.

After a hazard assessment of a job site, the Safety Director may determine that conditions may develop that could possibly warrant an evacuation. In this case, an emergency action plan will be developed to address the threat. Certainly, if work is being done at a hazardous chemical plant, for example, an emergency action plan is required and coordination will be made with the facility operator.

Events may occur which dictate the evacuation of a job site such as a fire, explosion, power failure, etc.. Additionally, events may occur which dictate the need for emergency medical responders. These sets of events fall under our Emergency Action Plan and a multitude of objectives must be met.

The first and foremost objective is the safety of all our personnel. To achieve this level of safety, our plan is designed to get personnel away from danger, treat injury, and provide for a thorough and accurate accounting of all employees.

There may be situations where certain employees, trained in first aid and/or firefighting procedures, may prevent a small emergency situation from becoming a major disaster. In these types of situations, specifically identified employees will remain to perform the function for which they are trained, provided they may perform these duties in a safe manner. At no time will any employee put himself/herself at risk.

To the extent possible, job sites will have clear, direct, egress.

The actual implementation of this plan must be direct and carried out without confusion. Employees must know how to alert others, how to call for assistance, the location of fire extinguishers and first aid kits, the escape route, and the rendezvous point (being accounted for so that others do not put themselves at risk looking for a person who has already reached safety).

## EMERGENCY MEDICAL RESPONSE

Should an injury occur that requires an emergency medical responder, the below listed actions will be taken in order given:

1. Call 911 or the emergency response number posted on the job site.
2. Provide any medical assistance you are trained and certified to do.  
**DO NOT** provide any medical assistance you are not trained to do.



3. Designate an individual to direct the emergency responders to the injured person and provide Material Safety Data Sheets if applicable.
4. Notify the competent person who, in turn, will notify the office.

### **FIRE PREVENTION PLAN**

Fire Prevention deals not with handling a fire emergency, but rather preventing a fire in the first place.

To reduce the likelihood of a fire, personnel are to adhere to the following rules:

1. Smoking is allowed only in designated areas and smoking materials will be totally extinguished and placed in the appropriate receptacles.
2. All chemical products will be handled and stored in accordance with the procedures noted on their individual MSDS.
3. Heat producing equipment will be properly maintained and operated per the manufacturer's instructions to prevent accidental ignition of combustible materials.
4. Precautions will be taken when working with an open flame (such as welding) and those areas will be made fire safe by removing or protecting combustibles from ignition.
5. Combustible liquids must be stored in approved containers.
6. Chemical spills must be cleaned up immediately. This is particularly important for combustible and reactive liquids. Damaged chemical containers and cleanup materials must be properly disposed.  
[Note: Exercise care! Information on appropriate personal protective equipment; proper disposal; proper cleanup procedures; required ventilation, etc. is found on the product's MSDS.]
7. Combustible liquids and trash must be segregated and kept from ignition sources.
8. Keep clear access to fire hydrants as well as portable fire extinguishers.
9. Personnel will be notified by their Supervisor or the competent person of any unusual fire hazard conditions existing on a job site.
10. Good housekeeping, good housekeeping!

### **PORTABLE FIRE EXTINGUISHERS**

All personnel will receive instruction on the proper use of fire extinguishers.

- a. Fire extinguishers will be inspected monthly for general condition and adequate charge. They will be serviced and certified by qualified personnel at least annually.
- b. Portable fire extinguisher locations will be clearly identified and easily accessible.

Portable fire extinguishers will be distributed as indicated below:

<u>CLASS</u>	<u>DISTRIBUTION</u>	<u>NOTES</u>
A "A" on a green triangle	75 feet or less travel distance between the employee and the extinguisher	Use on wood, paper, trash.
B "B" on a red square	50 feet or less travel distance between hazard area and the employee	Use on flammable liquid, gas.
C "C" on a blue circle	Based on the appropriate pattern for the existing Class A or Class B hazards	Use on electrical fires.
D "D" on a yellow star	75 feet or less travel distance between the combustible metal working area and the extinguisher or other containers of Class D extinguishing agent.	Use on combustible metals.

Appropriate portable fire extinguishers will be used, as noted above. Supervisors will ensure that at least one extinguisher is on each floor of a project near the stairway.

Using the wrong fire extinguisher on some fires can actually spread the fire. Using a Type A extinguisher on an electrical fire, for example, could cause serious injury. When a fire occurs, it is imperative to use the proper extinguisher.

## **FIRE PROTECTION**

The phone number of the local fire department shall be posted with other emergency numbers.

If a fire should occur, all personnel and the local fire department will be notified. As in all emergency situations, per the American Trauma Society, people calling the fire department should:

- a. Remain calm.
- b. Speak clearly and slowly.
- c. Give the exact location.
- d. Describe the situation.
- e. Give the phone number from where you are calling.
- f. Do not hang up until told to do so.

## FIRST AID & FIRST AID KITS

Should a medical emergency occur, other than minor scrapes and bruises, and it is serious enough to call for professional medical assistance, you should call the Emergency Response Number posted on the job site bulletin board. Before the first aid providers arrive, to the extent possible, clear the way so they can reach the injured employee in the most direct way possible.

Unless trained and licensed in CPR/first aid and a designated first aid provider as an additional job as part of the company bloodborne pathogen program, employees will not expose themselves to blood or other bodily fluids of other employees at any time.

Per OSHA, first aid is limited to:

- a. Using a non-prescription medication, such as aspirin, at non-prescription strength.
- b. Cleaning, flushing or soaking wounds on the surface of the skin;
- c. Using wound coverings such as bandages, Band-Aids™, gauze pads, etc.; or using butterfly bandages or Steri-Strips™.
- d. Using hot or cold therapy.
- e. Using any **non-rigid** means of support, such as elastic bandages, wraps, non-rigid back belts, etc..
- f. Using temporary immobilization devices while transporting an accident victim (e.g., splints, slings, neck collars, back boards, etc.).
- g. Drilling of a fingernail or toenail to relieve pressure, or draining fluid from a blister.
- h. Using eye patches.
- i. Removing foreign bodies from the eye using only irrigation or a cotton swab.
- j. Removing splinters or foreign material from areas other than the eye by irrigation, tweezers, cotton swabs or other simple means.
- k. Using finger guards.
- l. Using massages.
- m. Drinking fluids for relief of heat stress.

If an employee is injured and emergency responders have been called, stay calm and reassure the injured employee that help is coming.

Below is basic first aid for various common job site injuries. Mostly, it is what **not** to do.

## MINOR BURNS

(Redness or blisters over a small area)

Flush with cold water; apply a sterile dressing.

**Do not** use butter on any burn.

**Do not** break open blisters.

## MAJOR BURNS

(White or charred skin; blisters and redness over a large area; burns on face, hands, or genital area)

Cover with sterile dressing and seek medical attention promptly.

**Do not** apply salves, ointments or anything else.

**Do not** break blisters.

## CHEMICAL BURNS

(Spilled liquid or dry chemical on skin)

Liquid - Flush with large amounts of water immediately  
(keep water flow gentle).

Dry - Brush as much off as possible before flushing with water.

After flushing at least 5 minutes, cover with sterile dressing.

Seek medical attention promptly.

**Do not** use anything but water on burned area.

**Do not** break open blisters.

## EYE - FOREIGN OBJECT

(Object visible; feeling of something in the eye)

Have patient pull upper eyelid over lower eyelid.

Run plain water over eye.

If object does not wash out, cover both eyes with a gauze dressing.

Seek medical attention promptly.

**Do not** rub the eye.

## EYE - WOUNDS

(Wound on eyelid or eyeball; pain;  
history of blow to eye area; discoloration)

Apply loose sterile dressing over both eyes.

Seek medical help immediately.

For bruising, cold compress or ice pack may relieve pain and reduce swelling.

**Do not** try to remove any embedded object.

**Do not** apply pressure to eye.

EYE - CHEMICAL BURN  
(Chemical splashed or spilled in eye)

Flush immediately with water over open eye for at least 10 minutes (20 minutes if alkali). It may be necessary to hold patient's eyelid open.

Cover both eyes with sterile dressing.

Seek medical help immediately.

**Do not** put anything but water in eye.

HEAT EXHAUSTION

(Fatigue; weakness; profuse sweating; normal temperature; pale clammy skin; headache; cramps; vomiting; fainting)

Remove from hot area.

Have victim lay down and raise feet.

Apply cool wet cloths.

Loosen or remove clothing.

Allow small sips of water if victim is not vomiting.

HEAT STROKE

(Dizziness; nausea; severe headache; hot dry skin; confusion; collapse; delirium; coma and death)

Call for immediate medical assistance.

Remove victim from hot area.

Remove clothing.

Have victim lay down.

Cool the body (shower, cool wet cloths)

**Do not** give stimulants.

When dealing with any injury, stay calm and never do anything unless you know what you are doing.

**First Aid Kits:**

First aid kits are worthless if not readily accessible. Therefore, they will not be locked up on job sites.

First aid kits will be replenished as items are used. Sterile items will be wrapped and sealed and used only once. Other items such as tape or scissors can be reused and should be kept clean. In the absence of plentiful amounts of clean water, eye flush will be available.

The number of first aid kits to be found on the job site should be:

<u>Number of Persons Assigned to Job Site</u>	<u>Minimum First Aid Supplies</u>
1 - 5	10 Package Kit
6 - 15	16 Package Kit
16 - 30	24 Package Kit

Depending on the job site, first aid supplies will generally include: adhesive bandages, bandage compresses, scissors and tweezers, triangular bandages, antiseptic soap or pads, eye dressing, and other items that a consulting physician may recommend. The main purpose of a bandage, the most commonly used item in a first aid kit, is not really to stop the bleeding, but to keep the wound clean.

The three most important things dealing with first aid kits are:

1. They must be readily accessible.
2. They must be appropriate for the job site work involved.
3. Personnel must know how to use the contents of the first aid kits.

First aid kits must be replenished as items are used. Those individual items that must be sterile must be wrapped and sealed and used only once. Other items such as tape or scissors can be reused and should be kept clean.

The supplies consumed in first aid kits can actually be used as a safety tool. For example, if a kit constantly needs replacement of bandages which have been used for minor cuts, there is an obvious problem that the cuts are happening in the first place. Actual trends can be established and corrective procedures initiated such as protective gloves or handling practices.

Improper medical treatment can be more dangerous than no treatment at all.

## **SANITATION**

### **SANITATION. - 1926.51**

#### **Potable Water:**

From a safety standpoint, you must not neglect your need for potable (drinkable) fluids. Water is not only the most abundant of all compounds found on the earth, it is the most abundant part of you -- actually about 65% of you is water.

On construction sites, exertion and heat dictate the need for plenty of water.

Potable water will be available on job sites. If portable containers are used, they will be clearly marked [Potable Water]; capable of being tightly closed; and equipped with a tap. These containers will be used for no other purpose than supplying drinking water. Non-reusable (single service) cups in a sanitary container will be provided drinking as well as a receptacle for disposing of used cups. Employees are reminded of their need for adequate amounts of water.

**Non-Potable Water:**

Outlets of non-potable water should be clearly identified as such, through appropriate signage, and non-potable water may never be used for drinking, washing, or cooking.

**Toilets:**

Toilets will be provided at construction sites according to the below table:

<b>Number of Employees</b>	<b>Minimum Number of Facilities</b>
<b>20 or less</b>	<b>1</b>
<b>20 or more or more</b>	<b>1 toilet seat and 1 urinal per 40 workers</b>
<b>200 or more</b>	<b>1 toilet seat and 1 urinal per 50 workers</b>

Toilet facilities would include, unless prohibited by local law:

- a. Privies (where their use will not contaminate ground or surface water)
- b. Chemical Toilets
- c. Recirculating toilets
- d. Combustion toilets

**Washing Facilities:**

Adequate washing facilities will be provided in near proximity to the worksite if employees are working with contaminants that may be harmful to their health such as paint, coatings, or other chemical products. Paper towels and cleansing agents will be provided.

Showers and change rooms will be dictated by specific standards dealing with specific toxic materials (i.e., lead; asbestos).

**Eating and Drinking Areas:**

No employee will be allowed to consume food or beverages in any area exposed to toxic material.

**LIFTING, PUSHING & PULLING**

Back injuries are often caused by the obvious -- putting excessive strain on the lower back by lifting an object that is too heavy or awkward, or by bending and/or twisting while lifting.

However, lifting injuries are also caused by less obvious reasons:

- a. poor physical condition
- b. poor posture
- c. poor judgment (lifting, pulling, pushing an object that is obviously too heavy or awkward without seeking assistance or a mechanical lifting device.)
- d. lack of exercise
- e. excessive body weight

Proper lifting techniques are important for employee safety. Below are lifting techniques that will reduce the likelihood of injury:

- a. lift objects comfortably, not necessarily the quickest or easiest way.
- b. lift, push, and pull with your legs, not your arms or back.
- c. when changing direction while moving an object, turn with your feet, not by twisting at the waist.
- d. avoid lifting higher than your shoulder height.
- e. when standing while working, stand straight.
- f. when walking, maintain an erect posture; wear slip-resistant, supportive shoes.
- g. when carrying heavy objects, carry them close to the body and avoid carrying them in one hand.
- h. when heavy or bulky objects need to be moved, obtain help or use a mechanical aid such as a dolly, hand truck, forklift, etc..
- i. when stepping down from a height of more than eight inches, step down backwards, not forward.
- j. handle heavy objects close to the body -- avoid reaching out.
- k. lift gradually and smoothly. Avoid jerky motions.
- l. maintain a clear line of vision.

### **SLIPS, TRIPS & FALLS**

Slips, trips, and falls are among the most common job site accidents and they are easily preventable. Below are some of the causes of slips, trips, and falls:

- a. running on the job site.
- b. engaging in horseplay.
- c. working off a ladder that is not firmly positioned.



- d. carrying an object that blocks line of vision.
- e. work boots not laced or buckled.
- f. working off a scaffold without safety rails.
- g. using ladders that have oil and grease on the rungs.
- h. not using a handrail on steps.
- i. messy work areas with debris strewn about.
- j. not paying attention to what one is doing.

This list can go on and on, but all the above are easily preventable by adherence to common safety procedures, common sense, and awareness of potential hazards on the job site.

## **DRUGS AND ALCOHOL**

With the exception of over the counter drugs such as aspirin or drugs prescribed by a physician, there shall be no drugs or alcohol on any job site. Alcohol and drug abuse cause an unacceptable level of safety hazard not only for the offending employee, but for others in the vicinity. Those found to be under the influence of drugs and/or alcohol will be immediately removed from the job site by the competent person and further disciplinary action will be taken by the Safety Director.

Employees taking prescription medication that reduces motor skills should report this to their supervisor for appropriate work assignment.

Chemical dependency is a devastating problem for not only the employee, but also the employee's family and co-workers. For obvious safety reasons, it cannot be tolerated in the workplace. Those with such a problem should seek professional help. The Safety Director will assist any employee in finding appropriate treatment should they voluntarily come forward.

## **SMOKING**

There shall be no smoking except in designated smoking areas. Under no circumstances will there be smoking during refueling of vehicles or within 50 feet of flammable materials.

## **ACCIDENT INVESTIGATION**

The purpose of Accident Investigation is to prevent the same type of accident from reoccurring. An accident investigation will begin immediately after the medical crisis is resolved. The competent person/supervisor on the job site will complete an Accident Investigation Form as soon as feasible. The five questions that must be answered are: Who? What? When? Where? and most importantly, Why did the accident happen?

Apparently simple accidents may actually be caused by many complex reasons. Example: a worker is using a claw hammer on a working surface more than six feet above the ground. The hammer head breaks off and strikes a worker below who is not wearing a hard hat. Why did this accident happen? How can it be prevented? With just the facts presented, the fault would seem to rest with the worker who was struck by the falling object. Accident investigation may reveal other contributing factors by answering questions like:

- a. Were hard hats required on the project, were they available, and was this policy enforced by the supervisors?
- b. Were precautions taken to prevent objects from falling from above, such as a controlled access zone (CAZ)?
- c. Did the worker inspect his hammer before use? Was he driving nails -- the job for which a claw hammer is designed -- or pounding metal beams?

After determining the cause of the accident, steps can be taken to prevent a reoccurrence. Near-miss mishaps, events which result in no injury or damage, should be investigated because even though the outcomes are different, the causes are the same.

## **POSTINGS**

On every job site there will be a prominently displayed bulletin board or area for postings. Every employee must be aware of this policy. Certain postings are required as a matter of law in all cases and other postings are required depending on circumstances and types of work being done.

In all cases, the following must be posted to meet OSHA requirements:

- a. OSHA Form 3165, *It's the law!*
- b. During the period from 1 February through to April 30, OSHA Form 300A, *Summary of Work-Related Injuries and Illnesses*, must be posted for work-related injuries and illnesses which have occurred during the previous year.
- c. Emergency phone numbers and site address for emergency response.

If appropriate, the following must be posted:

- a. OSHA citations.
- b. Notice of informal hearing conference.
- c. Names and location of assigned first aid providers.
- d. Air or wipe sampling results.
- e. Emergency action plan.

## **RECORDKEEPING: INJURIES & ILLNESSES**

### **OSHA Forms 300; 300A & 301**

As a matter of law, all employers with 11 or more employees **at any one time** in the previous year must maintain OSHA Form 300, *Log of Work-Related Injuries and Illnesses*, OSHA Form 301, *Injury and Illness Incident Report*, and OSHA Form 300A, *Summary of Work-Related Injuries and Illnesses*.

OSHA Forms 300 and 301 are used to record and classify occupational injuries and illnesses. The information on the OSHA Form 300 related to employee health and must be used in a manner that protects the confidentiality of the employees to the extent possible. Recordable injuries and illnesses must be entered on OSHA Forms 300 and 301 within seven (7) days of receiving information that a recordable injury or illness has occurred.

#### **Retention of Forms:**

Old OSHA Forms 101 and 200 as well as OSHA Forms 300 and 301 will be retained for five years following the year to which they relate.

#### **Items to be recorded on OSHA Forms 300, 300A and 301:**

Work related injuries and illnesses and fatalities are to be recorded using the criteria found in Part 1904, *Recording and Reporting Occupational Injuries and Illnesses*.

Injuries and illnesses must be recorded if they result in death, days away from work, restricted work or transfer to another job, medical treatment beyond first aid, loss of consciousness, or if the injury or illness involves a significant injury diagnosed by a physician or licensed health care professional even if it does not meet the forgoing conditions.

NOTE: First aid (which is not reportable) is defined in 1904.7(b)(5)ii.

#### **Employee Involvement:**

As a matter of policy, all work-related accidents and injuries are to be immediately reported to the competent person/supervisor on a job site who will complete an accident investigation form. This will be forwarded to the Safety Director who will extrapolate appropriate information for completion of the OSHA Form 300.

#### **Catastrophic Reporting Requirements:**

Within eight (8) hours after the death of any employee from a work-related incident or the in-patient hospitalization of three (3) or more employees as a result of a work-related incident, either in person or by telephone, the OSHA

Area Office nearest to the site of the incident will be notified. OSHA may be contracted for this purpose using a toll free telephone number: 1-800-321-6742.

#### Location of OSHA Forms 300 and 301:

As a general rule, the OSHA Forms 300 and 301 will be maintained in our main office. However, in the event that a project is to last more than one year, that job site will be considered a fixed establishment and maintain its own OSHA Forms 300 and 301.

### **INCIDENCE RATE**

One indication of the success of our safety effort is our “incidence rate”. When bidding a job, our incidence rate could be a determining factor in a successful bid. The incidence rate is determined by the following formula:

$N/EH \times 200,000$  where:

N = number of injuries and/or illnesses

EH = total hours worked by all employees during the calendar year.

200,000 = base for 100 full-time equivalent workers  
(working 40 hours per week, 50 weeks per year).

To find the “Lost Workday Injury Rate” (LWDI), the following formula is used:

$LWDI \text{ Rate} = (\# \text{ LWDI's} \times 200,000) / \# \text{ employee hours worked}$

# LWDI = sum of LWDI's in reference years

# employee hours worked = sum of employee hours in reference years

200,000 = base for 100 full-time equivalent workers  
(working 40 hours per week, 50 weeks per year).

When accidents and injuries occur, they have an immediate detrimental impact on those employees involved. Additionally, they have a potential lingering negative impact on our company and our ability to get work.

### **SAFETY MEETINGS**

Scheduled safety meetings provide an opportunity for reinforcing the importance of general safety as well as specific work related procedures applicable to the work at hand. Properly prepared safety meetings will focus on one or two topics and be direct and to the point. All safety questions will be addressed and interactive participation is encouraged.

## ENFORCEMENT

It is expected that all employees will abide by our safety rules and guidelines not only to protect themselves, but also to protect their fellow workers from harm. Should a safety violation occur, the following steps will be taken by the employee's immediate supervisor:

- a. **Minor Safety Violations:** Violations which would **not** reasonably be expected to result in serious injury.
  1. The hazardous situation will be corrected.
  2. The employee will be informed of the correct procedures to follow and the supervisor will ensure that these procedures are understood.
  3. The supervisor will make a written report of the occurrence using our Enforcement Documentation Form and inform the employee that this documentation will be forwarded to the Safety Director for a retention period of one year.
  4. A repeat occurrence of the same minor safety violation is considered substantially more serious than the first.
- b. **Major Safety Violations:** Violations which would reasonably be expected to result in serious injury or death.
  1. The hazardous situation will be corrected.
  2. The employee will be informed of the correct procedures to follow and will impress upon the individual the severity of the violation and the likely consequences should this type of violation be repeated. The supervisor will ensure that the individual understands the correct procedures and will be cautioned that a reoccurrence could result in disciplinary action up to and including discharge.
  3. The supervisor will make a written report of the occurrence using our Enforcement Documentation Form and inform the employee that this documentation will be forwarded to the Safety Director for a retention period of one year.
- c. **Willful Major Safety Violations:** Intentional violation of a safety rule which would reasonably be expected to result in serious injury to the employee or a fellow worker.
  1. The hazardous situation will be corrected.

2. The employee will be removed from the job site, the event will be documented and forwarded to the Safety Director, and the employee will be discharged.

Employees are to understand that the primary purpose of documenting safety violations is to ensure that the important business of employee safety is taken seriously and that the potential for injury is reduced to the lowest possible level.

### **Schedule of Enforcement Actions for Violations within a 1 Year Period**

#### **Minor Violation**

<b>Offense</b>	<b>Action</b>	<b>Repeat of Same Offense</b>	<b>Action</b>
1st	Written Notice	1st	1 Day Off
2nd	Written Notice	2nd	3 Days Off
3rd	1 Day Off	3rd	Dismissal
4th	2 Days Off		
5th	3 Days Off		
6th	Dismissal		

#### **Major Violation**

<b>Offense</b>	<b>Action</b>	<b>Repeat of Same Offense</b>	<b>Action</b>
1st	Written Notice	1st	4 Days Off
2nd	2 Days Off	2nd	Dismissal
3rd	4 Days Off		
4th	Dismissal		

**[This page is intentionally left blank]**

# JOB SPECIFIC - EQUIPMENT SPECIFIC SAFETY PROCEDURES

## ABRASIVE WHEELS

### Abrasive wheels and tools. - 1926.303

An abrasive wheel is defined as a cutting tool consisting of abrasive grains held together by organic (resin, rubber, shellac or similar bonding agent) or inorganic bonds. Hazards that present themselves during abrasive wheel operations include physical contact with the rotating wheel; destruction of the wheel, itself; inhalation of the bonding particles; being struck by flying fragments. All these hazards can be eliminated through adherence to appropriate machine guarding principles, appropriate PPE, and/or respiratory protection.

Immediately before mounting, wheels must be inspected and sounded (ring test) to ensure they have not been damaged. Ensure the spindle speed does not exceed the maximum operating speed noted on the wheel.

**Ring Test:** Wheel to be tested must be dry and free from sawdust. Wheels should be tapped gently with a light nonmetallic implement, such as the handle of a screwdriver, or a wooden mallet for heavier wheels. If they sound cracked (dead), they may not be used. It should be noted that organic bonded wheels do not emit the same clear metallic ring as do vitrified and silicate wheels. Tap the wheels about 45° each side of the vertical centerline and about one or two inches from the periphery. Rotate the wheel about 45° and repeat the test. A sound, undamaged, wheel will give a clear metallic tone.

### **Guarding: Abrasive Blades in Portable Circular Saws:**

It is important to distinguish between a saw and an abrasive blade because they have different guarding requirements. An abrasive wheel, as defined by CFR §1910.211(b)(14) and American National Standards Institute (ANSI) B7.1-1970, as "a cutting tool consisting of abrasive grains held together by organic or inorganic bonds."

If a wheel is, for example, constructed with bonded, steel fragments arranged in intermittent clusters around the periphery of a steel disc, the steel fragments are too large and sharp to be considered abrasive grains. If these fragments remove material primarily by severing rather than by abrasion, then this would be considered a saw blade and the guarding requirements would be found in 29 CFR 1926.300, General Requirements.

If, in fact, cutting is done by the abrasive action of the abrasive grains, guarding requirements are found in 29 CFR 1926.303(b), Abrasive Wheels and Tools.

ANSI B7.1 requires the upper half of the abrasive blade to be guarded when abrasive wheels are installed on portable power driven circular saws.



## **AERIAL LIFTS**

### **Aerial lifts. - 1926.453**

Aerial lifts acquired for use which were manufactured on or after January 22, 1973 will have a placard or label affixed which indicates that the lift is designed and constructed in accordance with ANSI standard A92.2-1969. Aerial lifts acquired for use prior to January 22, 1973 may not be used unless modified to meet this standard. Aerial lifts may be modified to perform other than originally designed tasks provided the modifications are certified by the manufacturer or a nationally recognized testing laboratory that the aerial lift conforms with ANSI standard A92.2-1969 and is as safe as before modifications.

Aerial lifts include the following types of vehicle-mounted aerial devices to elevate personnel to job-sites above the ground:

- a. extensible boom platforms.
- b. aerial ladders.
- c. articulating boom platforms.
- d. vertical towers.
- e. a combination of any of the above.

Only authorized persons may operate an aerial lift.

Lift controls and equipment must be inspected and tested each day prior to use to determine they are in a safe working condition.

When working from an aerial lift, you must stand firmly on the floor of the basket or cage and **use (wear) and an approved fall restraint system**. The fall restraint system must be attached to the boom or basket – it may not be attached to any adjacent pole, structure, or other equipment. You may not sit or climb on the edge of the basket; use planks, ladders, or other devices for a work position.

Load limits set by the manufacturer must never be exceeded.

The brakes must be set and when outriggers are used, they shall be positioned on pads or a solid surface.

Aerial lifts must not be moved with personnel in the basket unless it is designed for this type of operation. Aerial lifts designed as personnel movers must have controls that are clearly marked as to their use and the lower controls must be able to override the upper controls. Except in an emergency, the lower controls shall not be used unless permission has been granted by the persons in the lift.

It is required that the vehicle have a “reverse signal alarm” audible above the surrounding noise level **or** a ground-guide (spotter), using standard hand signals, when backing up. The vehicle will be backed up only when

the spotter signals that it is safe to do so. Using a ground-guide provides a substantially higher level of safety than a “reverse signal alarm” because the vehicle can be guided to an exact location with assurance that there is sufficient clearance from objects, and, most importantly, no person is in harm’s way. Special attention will be given to avoiding contact with electrical lines.

## **COMBUSTIBLE & FLAMMABLE LIQUID HANDLING**

### **Flammable and combustible liquids. - 1926.152**

Only approved containers and portable tanks will be used for storage and handling of flammable and combustible liquids. Approved safety cans or Department of Transportation approved containers will be used for handling and use of flammable liquids in quantities of 5 gallons or less.

**Note 1: The above does not apply to flammable liquid materials which are highly viscid (extremely hard to pour) which may be used and handled in their original shipping containers.**

**Note 2: For quantities of one gallon or less, the original container may be used for storage, use and handling.**

Flammable or combustible liquids may not be stored in areas used for exits, stairways, or normally used for the safe passage of people.

Inside a facility, no more than 25 gallons of flammable or combustible liquids may be stored in a room outside of an approved storage cabinet.

### **GASOLINE: General Information**

Because most persons use or indirectly handle gasoline on a regular basis -- from filling up automobiles to lawn mowers -- the hazards presented by this product may have become obscure. Just because you are familiar with gasoline, never lose sight of the lethal hazards that it may contain.

Gasoline is a flammable liquid which means it has a flash point of less than 100°F. The actual flash point -- lowest temperature at which a liquid gives off enough vapor to form a flammable mixture with air -- of gasoline is - 45°F. The autoignition temperature -- the temperature at which, with sufficient oxygen, gasoline will ignite on its own and burn -- is 536°F.

Gasoline has a specific gravity -- the weight of the gasoline compared to the weight of an equal volume of water -- of 0.73. Further, gasoline has a negligible solubility in water. Basically, what the above means is that if water is used to extinguish a gasoline fire, it will only spread it because the gasoline will float on the water and continue to give off a vapor and form a flammable mixture with air. Gasoline fires must be fought with an extinguisher that is rated for Class B Fires such as carbon dioxide, dry chemical, or foam. It should be noted that water spray may be used to cool

containers that may be exposed to the heat of the fire to prevent an explosion.

Conditions to avoid: heat, flame, & sources of ignition. Materials to avoid: strong oxidizers.

Health hazard information: routes of entry: inhalation, skin, ingestion.

Signs & symptoms of overexposure: headache, nausea, drowsiness, breathlessness, fatigue, convulsions, loss of conscience, dermatitis.

If there is a spill, notify emergency response personnel, evacuate area, remove ignition sources, build a dike to contain flow, do not flush to sewer or open water. Pick up with inert absorbent and place in closed container for disposal.

Gasoline is a carcinogen -- a cancer causing agent.

General rules: Post "No Smoking" signs around gasoline storage and ensure that it is enforced. Use only approved plastic or metal containers for portable gasoline carriers. They must not contain more than 5 gallons.

Double check with local ordinances for storage requirements.

## **COMPANY VEHICLES**

Only authorized employees may operate, in the course of their work, any company-owned motor vehicle.

Prior to authorization, the employee must possess a valid and current license to operate the vehicle. The Safety Director, or authorized representative, will ensure that the employee has demonstrated his/her ability to operate the motor vehicle in a safe and competent manner.

Under no circumstances may any motor vehicle be operated under the influence of alcohol, illegal drugs, or prescription or over-the-counter drugs medications that may impair their driving skills.

When driving over the road vehicles, employees will ensure that the vehicle registration and proof of insurance is within the vehicle. In the event of an accident, the Safety Director will be notified **immediately** after all potential injuries are addressed and a police report is filled out. Employees must report all traffic violations to the Safety Director and they are responsible for paying all penalties imposed by law.

Loads in vans and trucks will be properly secured [strapped or blocked] to preclude any shift or movement and care will be taken to not exceed the vehicles weight limits.

All company motor vehicles will be maintained in safe operating condition and in accordance with the manufacturer's recommended maintenance schedule.

A log book will be maintained for each vehicle and receipts will be kept for all maintenance and repairs performed.

Before use, a walk around inspection will be performed by the operator checking tires (tread depth and pressure), glass (chips and cracks), horn and lights, and general vehicle condition. Discrepancies will be noted in the log book. No vehicle will be operated that is not in safe mechanical condition. It is expected that the below safe vehicle operation/driving procedures will be followed at all times:

1. Seat belts will be worn by all occupants at all times while the vehicle is in motion.
2. Safe distance [one vehicle length per 10 MPH] will be maintained.
3. Posted speed limits will not be exceeded.
4. During fuel stops, all fluids will be checked and the windows, headlights and taillights will be cleaned.
5. Constant attention will be maintained by always being aware of road conditions and surrounding vehicles. Unnecessary distractions will not be permitted such as using hands to dial or receive cell phone calls or changing radio stations while the vehicle is in motion. Hands free cell phone use is allowed.
6. Before backing up any vehicle, check behind and blow horn for the safety of others.

## **COMPRESSED GAS CYLINDERS**

### **Gas welding and cutting. - 1926.350**

#### **Compressed Gas Cylinders Use:**

Compressed gas cylinders are used on many job sites -- the most common being oxygen and acetylene for welding.

Failure to follow basic safety procedures could result in serious injuries such as:

- a. flash burn - due to explosion.
- b. fragment impalement - due to explosion.
- c. compression of the foot - due to mishandling of tanks.
- d. inhalation of hazardous gases - due to leakage.

All employees who use compressed gas cylinders will be trained in their proper storage, handling, and use.

Specific requirements for compressed gas cylinders use include:

1. Compressed gas cylinders will be clearly marked to identify the gas contained therein. Gas identification must be stamped or stenciled on the gas cylinder or a label affixed. No gas cylinder will be accepted for use that does not legibly identify its content by name.
2. Visual or other inspections will be performed by the competent person on site to ensure the compressed gas cylinders are in a safe condition.
3. Compressed gas cylinders will be inspected to ensure they are equipped with the correct regulator. Before use, regulators and cylinder valves will be inspected to ensure they are free from oil, dirt, and solvents.
4. Compressed gas cylinders will have valve protectors in place when not in use **or** connected for use.
  - a. When a cylinder cap cannot be removed by hand, the cylinder will be tagged “**Do Not Use**” and returned to the designated storage area for return to the vendor.
5. The user of the compressed gas cylinders will use **only the tools supplied by the provider** to open and close cylinder valves.
6. Valves will be closed before the cylinder is moved, when the cylinder is empty, and at the completion of each job.
7. Leaking cylinders will be moved to an isolated, well-ventilated area, away from ignitions sources.

**Note:** Soapy water will be used to detect the exact location of the leak. If the leak is at the junction of the cylinder valve and cylinder, do not attempt to repair it. The supplier will be contacted and asked for proper response instructions.

8. Gasses may never be mixed in a cylinder. **Only professionals may refill gas cylinders.**
9. Hoses and connections will be inspected regularly for damage. Hoses should be stored in cool areas and protected from damage.

### **Compressed Gas Cylinders Storage**

1. Cylinders must be secured at all times in such a way as to avoid them being knocked over or damaged. They must be stored in a vertical position. They must be segregated based on contents. 20 feet should be maintained between oxidizers and flammables or firewalls erected at least 5 feet high with a fire rating of 30 minutes.
2. Cylinders must be protected from damage, corrosion, sunlight.
3. Cylinders must be stored in well protected, well ventilated, dry locations away from sunlight. Cylinders will never be kept in unventilated enclosures such as lockers or cupboards.

4. Cylinders must be stored away from stairs, elevators, and gangways.
5. Clearly designated and labeled **separate storage area** will be provided for **full and empty** cylinders.
6. Empty cylinders that are no longer needed must be marked as “MT” and dated when empty. Empty cylinders must be handled as carefully as full cylinders.
7. Cylinders will be capped when they are not being used

### **Transportation of Compressed Gas Cylinders**

1. Compressed gas cylinders must be transported in a vertical secured position using a cylinder basket or cart.
2. Regulators should be removed and cylinders capped before movement.
3. Cylinders may never be rolled. Cylinders should not be dropped or permitted to strike violently.
4. Protective caps are not to be used to lift cylinders.

## **CRANES**

**Note:** The below information is applicable to the following crane types and operations:

1. **Articulating/knuckle-boom truck cranes that deliver material to a construction site when used to transfer materials from the truck crane to the ground, without arranging the materials in a particular sequence for hoisting.**
2. **Articulating/knuckle-boom truck cranes that deliver material to a construction site when the crane is used to transfer building supply sheet goods or building supply packaged materials from the truck crane onto a structure, using a fork/cradle at the end of the boom, but only when the truck crane is equipped with a properly functioning automatic overload prevention device. Such sheet goods or packaged materials include, but are not limited to: sheets of sheet rock, sheets of plywood, bags of cement, sheets or packages of roofing shingles, and rolls of roofing felt.**

**Note:** The above articulating/knuckle-boom crane exclusion does not apply when it is used to 1) hold, support or stabilize the material to facilitate a construction activity, such as holding material in place while it is attached to the structure; 2) when the material being handled is a prefabricated component such as precast concrete members or panels, roof trusses, prefabricated building sections such as, but not limited to: floor panels, wall panels, roof panels, roof structures, or similar items; and, 3) when the material being handled by the crane is a structural steel member (for example, steel joists, beams, columns, steel decking (bundled or unbundled) or a component of a systems-engineered metal building.

All other crane operations fall under Subpart CC—Cranes and Derricks in Construction. **Our program that address Cranes and Derricks in Construction is found in Section III of this safety program.**

Cranes, like all pieces of heavy equipment, if not properly operated, inspected and maintained have a potential for causing major bodily injury or property damage. Care must be taken in all facets of crane operation. Not only do cranes require a thorough annual inspection (a record of the dates and results of these inspections must be maintained), they require inspection prior to each use and even during use by a competent person. All rated load capacities, recommended operating speeds, special hazard warnings or instructions must be readily visible to the operator of the crane. While cranes easily have the lifting ability to hoist employees on a personnel platform, this is absolutely prohibited except in cases when the erection, use, and dismantling of conventional means of reaching the worksite would be more hazardous or is not possible because of structural design or worksite conditions. A conventional means would include: a personnel hoist, ladder, stairway, aerial lift, elevating work platform or scaffold.

It is absolutely imperative that the possibility of electrocution be totally eliminated. This can be accomplished by adhering to the safe distances from various currents noted in *Heavy Equipment and Electrical Power Lines*, below.

Dangers associated with cranes include numerous moving parts. These dangers can be minimized or eliminated by ensuring that all guards are in place and not tampered with.

Care must be taken to ensure that areas within the swing radius of the rear of the rotating superstructure of the crane are barricaded to prevent a person from being struck or crushed.

All employees must keep clear of loads that are about to be lifted as well as suspended loads.

When using slings made from alloy steel chain, wire rope, metal mesh, natural or synthetic fiber rope (conventional three strand construction), and synthetic web (nylon, polyester, and polypropylene), the following safe operating practices will be observed:

- a. Slings shall not be shortened with knots or bolts or other makeshift devices.
- b. Sling legs shall not be kinked.
- c. Slings used in a basket hitch shall have the loads balanced to prevent slippage.
- d. Slings shall be padded or protected from the sharp edges of their loads.
- e. Hands or fingers shall not be placed between the sling and its load while the sling is being tightened around the load.

Hand signals used to guide the crane operator will be consistent with the ANSI standard for the type of crane in use and an illustration of the signals must be posted at the job site.

Care must be taken while actually operating the crane in hoisting applications as well as when relocating the crane superstructure.

The competent person on site will ensure that the flooring on which equipment may be placed is substantial enough to safely hold the weight of the load. If the strength of the floor is unknown and/or cannot be determined, a professional engineer will determine the pounds per square foot required and, if necessary, the appropriate shoring to be installed to sustain the weight.

## **DEMOLITION**

**Preparatory operations. - 1926.850**

**Stairs, passageways, and ladders. - 1926.851**

**Chutes. - 1926.852**

**Removal of materials through floor openings. - 1926.853**

**Removal of walls, masonry sections, and chimneys. - 1926.854**

**Manual removal of floors. - 1926.855**

**Removal of walls, floors, and material with equipment. - 1926.856**

**Storage. - 1926.857**

**Removal of steel construction. - 1926.858**

**Mechanical demolition. - 1926.859**

**Selective demolition by explosives. - 1926.860**

Demolition work presents specific hazards that are not normally found on typical job sites. These hazards include, but are not limited to:

- a. the actual collapse of the structure being demolished. Prior to demolition operations, a competent person must determine, and document in writing, the condition of the framing, floors, and walls, and assess the possibility of an unplanned collapse of any portion of the structure. If appropriate, adjacent structures where employees may be exposed to danger must be checked by a competent person.
  1. wall and floors must be braced or shored if employees must work in a structure to be demolished that has been damaged by fire, flood, explosion.
- b. explosion, electrocution, hazardous atmospheres. Prior to demolition work all electric, gas, water, steam, sewer, and other service lines must be shut off, capped, or otherwise controlled, outside the building line before demolition work is started. In each case, any utility company which is involved shall be notified in advance.
  1. additionally, the competent person must determine if hazardous chemicals, gases, explosives, flammable materials, etc. are in



pipes, tanks, or other equipment on the property. If apparent or suspected, testing and purging must be performed and the hazard eliminated before demolition is started. It is not uncommon during the demolition of older structures to have potential asbestos and/or lead exposure.

**Note: If an abatement contractor has abated materials from a building that we are to demolish, we will obtain written certification from the abatement contractor certifying that all the materials in question have been properly removed and appropriate air and/or wipe clearance testing has been completed.**

- c. shattered glass.
- d. falling debris.
- e. falling through holes or wall openings.

Specific procedures to eliminate employee hazard exposure during demolition operations are found in the standards immediately following this Section. Areas that are addressed include: stairs, passageways, and ladders; chutes; removal of materials through floor openings; removal of walls, masonry sections, and chimneys; manual removal of floors; removal of walls, floors, and material with equipment; storage of waste material; removal of steel construction; and mechanical demolition.

### **DISPOSABLE RESPIRATORS**

OSHA requires that employees who voluntarily use disposable respirators in situations where respiratory protection is not specifically required by OSHA standard (in atmospheres where exposures are below the permissible exposure limit) essentially for personal comfort or additional, though not required, respiratory protection be informed of 29 CFR 1910.134 Appendix D, printed below.

By insisting that these employees sign the tear-off employee handbook acknowledgement form, you can protect your company from OSHA citation for violating this requirement.

All disposable respirators, such as Moldex, 3M, Wilson, North Safety, etc. must be marked with the manufacturer's name, the part number, the protection provided by the filter, and "NIOSH".

Disposable filters are particulate respirators. They are also known as "air-purifying respirators" because they protect by filtering particles out of the air you breathe.

The below outlines the types of approved disposable respirators and their description.

N95	Filters at least 95% of airborne particles.	Not resistant to oil.
N99	Filters at least 99% of airborne particles.	Not resistant to oil.
N100	Filters at least 99.7% of airborne particles.	Not resistant to oil.
R95	Filters at least 95% of airborne particles.	Somewhat resistant to oil.
P95	Filters at least 95% of airborne particles.	Strongly resistant to oil.
P100	Filters at least 99.7% of airborne particles.	Strongly resistant to oil.

Though disposable filters cannot be fit-tested in the traditional sense, they must be fit-tested in accordance with the manufacturer's instructions.

Under no circumstances may any respirator other than the above disposable respirators be used without compliance with a respiratory protection program.

**Standard Number: 1910.134 App D**

**Standard Title: (Mandatory) Information for Employees Using  
Respirators When not Required Under Standard.**

Respirators are an effective method of protection against designated hazards when properly selected and worn. Respirator use is encouraged, even when exposures are below the exposure limit, to provide an additional level of comfort and protection for workers. However, if a respirator is used improperly or not kept clean, the respirator itself can become a hazard to the worker. Sometimes, workers may wear respirators to avoid exposures to hazards, even if the amount of hazardous substance does not exceed the limits set by OSHA standards. If your employer provides respirators for your voluntary use, or if you provide your own respirator, you need to take certain precautions to be sure that the respirator itself does not present a hazard. You should do the following: 1. Read and heed all instructions provided by the manufacturer on use, maintenance, cleaning and care, and warnings regarding the respirators limitations. 2. Choose respirators certified for use to protect against the contaminant of concern. NIOSH, the National Institute for Occupational Safety and Health of the U.S. Department of Health and Human Services, certifies respirators. A label or statement of certification should appear on the respirator or respirator packaging. It will tell you what the respirator is designed for and how much it will protect you. 3. Do not wear your respirator into atmospheres containing contaminants for which your respirator is not designed to protect against. For example, a respirator designed to filter dust particles will not protect you against gases, vapors, or very small solid particles of fumes or smoke. 4. Keep track of your respirator so that you do not mistakenly use someone else's respirator.

[63 FR 1152, Jan. 8, 1998; 63 FR 20098, April 23, 1998]

## **ELECTRICAL WORK - WORKPLACE SAFETY**

**Applicability. - 1926.402**

**General requirements. - 1926.403**

**Wiring design and protection. - 1926.404**

**Special systems. - 1926.408**

**General requirements. - 1926.416**

**Definitions applicable to this subpart. - 1926.449**

All electrical work will be done according to the latest adopted National Electrical Code as well as established local codes.

### **ELECTRICAL SAFETY MEASURES**

- a. Daily, prior to use, all electrical equipment -- including extension cords -- will be inspected and defective items will be tagged out of service and not used.
- b. With the exception of double insulated tools (with UL approval), all electrical tools and equipment will be grounded.
- c. Tools will not be hoisted by their flexible electrical cords.
- d. Except in an emergency, load rated switches and circuit breakers will be used for the opening and closing of circuits under load conditions as opposed to fuses and splice connections.
- e. While working on electrical equipment, unauthorized persons will be kept clear by barriers or other means of guarding.
- f. Temporary wiring and extension cords will be kept off of walking working surfaces and vehicle traffic areas or covered to prevent tripping and vehicle damage.
  1. Electrical cords will not be suspended with staples, hung from nails, or suspended by wire.
  2. Worn or frayed electric cords or cables will not be used.
- g. Hands will be dry when working on electrical equipment including plugging in extension cords.
- h. Areas in which electrical work is to be done must be adequately illuminated and temporary lighting must:
  1. have guards in place.
  2. not be suspended by its cords unless specifically designed for such installation.
- i. A competent person, before work commences, will inform all employees in the work area of both exposed and concealed electrical hazards. If appropriate, warning tags will be used to prevent accidental contact with electrical energy.

- j. When working around any electrical power circuit, employees will:
  1. **protect themselves by deenergizing the circuit and grounding it or by establishing insulation between themselves and the current.**
  2. ensure that any conductive materials and equipment that are in contact with any part of their body will be handled in a manner that will preclude contact with exposed energized conductors or circuit parts.
  3. use portable ladders that have non-conductive siderails.
  4. remove or insulate conductive articles of jewelry and clothing that might contact exposed energized parts.
- k. All 15, 20, or 30 amp receptacle outlets that are not part of the permanent wiring of the building or structure and that are used by personnel shall have ground-fault circuit interrupter protection for personnel. GFCI pigtails may be used to meet this requirement if properly sized. Remember, extension cords are considered temporary wiring.
  1. Ground fault circuit interrupters will be tested before use.
- l. Only qualified persons may perform testing work on electric circuits or equipment.
- m. Sufficient access and working space must be maintained about all electric equipment to permit ready and safe operation and maintenance. This space must be kept clear, i.e., it can not be used for storage.
- n. The dimension of the working space in the direction of access to live parts likely to required examination, adjustment, service, or maintenance must not be less that noted below:

Working Clearances

Minimum clear distance for conditions<sup>1</sup>

<u>Nominal voltage to ground</u>	<u>(a) Feet<sup>2</sup></u>	<u>(b) Feet<sup>2</sup></u>	<u>(c) Feet<sup>2</sup></u>
0-150	3	3	3
151-600	3	3 ½	4

Footnote<sup>1</sup> Conditions (a), (b), and (c) are as follows:

- {a} Exposed live parts on one side and no live or grounded parts on the other side of the working space, or exposed live parts on both sides effectively guarded by insulating material. Insulated wire or insulated busbars operating at not over 300 volts are not considered live parts.

- {b} Exposed live parts on one side and grounded parts on the other side.
- {c} Exposed live parts on both sides of the workplace [not guarded as provided in Condition (a)] with the operator between.

### Minimum Depth of Clear Working Space in Front of Electric Equipment

<u>Nominal voltage to ground</u>	Conditions <sup>1</sup>		
	<u>(a)</u> <u>Feet<sup>2</sup></u>	<u>(b)</u> <u>Feet<sup>2</sup></u>	<u>(c)</u> <u>Feet<sup>2</sup></u>
601 to 2,500	3	4	5
2,501 to 9,000	4	5	6
9,001 to 25,000	5	6	9
25,001 to 75 kV	6	8	10
Above 75kV	8	10	12

Footnote<sup>1</sup> Conditions (a), (b), and (c) are as follows:

- {a} Exposed live parts on one side and no live or grounded parts on the other side of the working space, or exposed live parts on both sides effectively guarded by insulating materials. Insulated wire or insulated busbars operating at not over 300 volts are not considered live parts.
- {b} Exposed live parts on one side and grounded parts on the other side. Walls constructed of concrete, brick, or tile are considered to be grounded surfaces.
- {c} Exposed live parts on both sides of the workspace [not guarded as provided in Condition (a)] with the operator between.

1. The importance of working clearances cannot be overstated. At any time, when working with live electrical systems, there is the possibility of an arcing fault causing an arc flash where the current explosively flows through ionized air at 35,000°F causing incurable burns, hearing loss, collapsed lungs, or even death from the electricity of flying metal shrapnel.
2. As a contractor working in an area where the possibility of arc flash exists, check to see if an arc flash assessment has been performed on electrical equipment on which you will be working. If it has, follow that specific guidance. If it has not, perform (or have a qualified vendor perform) the arc flash assessment. Refer to NFPA 70E for specific guidance appropriate to the facility's specific electrical equipment.

**Note:** NFPA 70E is a National Consensus Standard which is incorporated by reference within the OSHA standards; specifically, Appendix A to Subpart S, 29 CFR 1910. Failure to comply with NFPA 70E is citable under the general duty clause.

The above electrical safety measures are not all inclusive, however they cover many normal job site events. A complete list is found in the cited references and they are incorporated into this safety manual. If in doubt about any safety procedure, contact your supervisor or the competent person for clarification.

## **EXTENSION CORDS**

**Wiring methods, components, and equipment for general use. - 1926.405**

**General requirements. - 1926.416**

Extension cords shall not replace permanent wiring and the following safety precautions will be adhered to:

- a. Inspect the cord for cracks and cuts.
- b. Cord must have a three prong plug for grounding.
- c. Use the shortest continuous length of cord possible. Cords may not be spliced together.
- d. Make certain the cord does not lay in water.
- e. Ensure cord is properly rated for the job.
- f. Secure and route cords out of the traffic flow to prevent tripping.
- g. Defective cords will be tagged and removed from service.
- h. Most importantly, an extension cord used on a job site **MUST** be used with a ground fault circuit interrupter (GFCI).

## **GROUND FAULT CIRCUIT INTERRUPTERS**

**Wiring design and protection. - 1926.404**

A ground fault circuit interrupter (GFCI) provides protection for all 120-volt, 15-, 20-, and 30-ampere receptacle outlets that are not a part of the permanent wiring by detecting lost current resulting from a short, overheating, and/or ground fault. It should be noted that an extension cord into which electrical devices are plugged are not part of the permanent wiring; therefore, GFCI's are required.

A GFCI will "trip" when the amount of current amperes going to an electrical device in the hot conductor and the amount of current returning from an electrical device differs by approximately 5 milliamps. The GFCI can interrupt the current within as little as 1/40th of a second.

The current that is missing is being lost through a ground fault, whether it is in the actual grounding, a short in the equipment or electricity going through the employee to the ground.

A GFCI will not protect an employee who comes in contact with two hot wires or a hot wire and a neutral wire. A GFCI will provide protection against fires, overheating, damage to insulation, and, the most common form of electrical shock hazard -- the ground fault. GFCI's must be tested before use.

## HEAVY EQUIPMENT AND ELECTRICAL POWER LINES

Except where electrical distribution and transmissions lines have been deenergized and visibly grounded at point of work or where insulating barriers (not attached to the vehicle) have been erected to prevent physical contact with the lines, the following clearance -- between any part of the equipment, load line, or load **and** the power line -- will be observed:

**Table A—Minimum Clearance Distances Per 29 CFR 1926. 1408 & 1409**

Voltage (nominal, kV, alternating current)	Minimum clearance distance(feet)
up to 50	10
over 50 to 200	15
over 200 to 350	20
over 350 to 500	25
over 500 to 750	35
over 750 to 1,000	45
over 1,000	(As established by the utility owner/operator or registered professional engineer who is a qualified person with respect to electrical power transmission and distribution).

Note: The value that follows “to” is up to and includes that value. For example, over 50 to 200 means up to and including 200kV.

A ground guide will be designated to observe clearance of the equipment and give warning to the equipment operator in situations where it is difficult for the equipment operator to maintain the desired clearances by visual means.

An overhead wire will be considered energized unless the owner of the line or the electrical utility authorities indicate that it is not energized and it has been visibly grounded.

## HOISTS

### **Material hoists, personnel hoists, and elevators. - 1926.552**

A hoist is a useful mechanical device which gives one the ability to lift and move heavy objects -- not people. No person is to ride on a hoist. As with all mechanical devices, improper use may lead to injury. You must know what you are doing and you must be careful.

Before use, hoists must be inspected for bent or damaged components. Particular attention should be paid to guarding. Fingers and loose clothing could be snagged in exposed mechanisms. Chains, cables, or rope slings must not be kinked, twisted, or frayed.

Loads must be properly rigged with hooks or slings and they must never exceed the hoist's rated capacity.

Ensure that the area around the hoist is free from debris and, most importantly, people. Do not allow yourself or others to be under a hoisted load.

## LIGHTING

### Illumination. - 1926.56

A competent person will ensure that all work areas have adequate lighting. Adequate lighting serves a two-fold purpose -- allowing tasks to be more readily performed as well as providing the additional safety factor of being seen by persons not involved with the work -- especially vehicular traffic.

If generators are used for auxiliary lighting, they will be operated and maintained by authorized persons who are competent by training or experience.

## LP-GAS STORAGE

### Liquefied petroleum gas (LP-Gas). - 1926.153

Liquefied petroleum gas (LP-Gas) is sometimes used on job sites to provide fuel for temporary heating devices.

LP-Gas systems must have containers, valves, connectors, manifold valve assemblies, and regulators of an approved type. All cylinders must be DOT approved.

Rules for inside storage (under construction standards) are simple -- **it is not allowed!**

**Note: Under industry standards, up to 300 pounds of LP-Gas may be stored, with adherence to specific safety procedures, is allowed**

Rules for outside storage require that containers be in a suitable ventilated enclosure or otherwise protected against tampering. At least one approved portable fire extinguisher having a rating of not less than 20-B:C must be readily available.

The distance from buildings or groups of buildings that containers must be stored are as follows:

<u>Quantity of LP-Gas Stored</u>	<u>Distance in Feet</u>
500 lbs or less	0
501 to 6,000 lbs	10
6,001 to 10,000 lbs	20
over 10,000 lbs	25

Storage must not be near building openings or vehicular traffic.

## LP-GAS TEMPORARY HEATING

### Liquefied petroleum gas (LP-Gas). - 1926.153

When LP-Gas is used for temporary heating on units that provide over 7,500 BTU per hour or use containers greater than 2.5 pounds maximum water capacity [nominal 1 pound LP-Gas capacity], the following will apply:

- a. Container valves, connectors, regulators, manifolds, piping and tubing must not be used as structural supports for the heaters.



- b. The LP-Gas containers and all associated equipment including hoses must be located so as to minimize exposure to high temperatures or physical damage.
- c. The maximum water capacity of individual containers must be 245 pounds [nominal 100 pound LP-Gas capacity].

Heaters that are not integral heater-container units, which connected by hose to the LP-Gas, must be at least 6' from the container. Blower and radiation type heaters must not be directed toward the container or any other unit within 20 feet. Heaters specifically designed for attachment to the container are permitted as long as the heat is not directed to the LP-Gas container.

## **MACHINE GUARDING**

### **Mechanical power-transmission apparatus. - 1926.307**

Most injuries that occur when operating a machine happen at the point of operation -- the point on a machine where the actual work (cutting, bending, spinning) occurs. This is also the point where guards can protect fingers and hands exposed to that danger. Machine guarding also protects employees from other dangers such as flying pieces of metal, sparks, gears, belts, and rotating parts.

The most common types of machines on job sites are power tools which often have guards to prevent injury.

Accident prevention in this area is a function of machine design -- engineering controls -- and operator training. Types of machine guarding are almost as numerous as types of machines -- the most common being a physical barrier to prevent accidental insertion of body parts. Guards are vital for safety reasons and machine guards designed into a machine should never be altered or removed. The speed and tremendous forces involved in modern machines are such that severe injury or even death could occur without warning and without even slowing the machine down.

Training and proper work methods go a long way toward reducing machine accidents. Like all safeguards, there is generally a way to bypass safety features that are engineered into machines. This is sometimes done to increase speed or just to make one's job easier. This could result in a tragic, avoidable accident. The few seconds saved could cause a lifetime of grief. Do not bypass safety systems.

Operate all machines according to the instructor's manual and follow all safety procedures.

## MACHINERY

Spinning, pounding, moving -- gears, pulleys, levers -- electricity, fuel, hydraulics -- action, reaction, force: danger! Machinery takes energy and performs a task or a multitude of tasks. Machinery, from a safety standpoint, is a collection of individual simple machines (pulleys, gears, etc.) combined to work in harmony to accomplish a specific job.

The danger is obvious: the power, speed, movement, and momentum of machinery is not going to be altered by something as insignificant as an employee's finger, hand, or even body.

How does one deal with the dangers of machinery? First, **never** operate any machinery until you have received proper training and you thoroughly understand safety procedures as well as procedures to follow for adjustments, power interruption, jamming, lubrication, and inspection.

Secondly, ensure the guarding systems are in place, functioning properly, and have not been altered or removed.

Thirdly, if a hazard assessment of the machinery operation dictates specific personal protective equipment (PPE), wear it!

Lastly, again from purely a safety standpoint, think of any power operated item with moving parts as machinery. This would include items as diverse as a small electric drill to an 80,000 pound tractor-trailer.

## RIGGING FOR MATERIAL HANDLING

### Rigging equipment for material handling. – 1926.251

**Note:** The below information is applicable to the following crane types and operations:

- 1. Articulating/knuckle-boom truck cranes that deliver material to a construction site when used to transfer materials from the truck crane to the ground, without arranging the materials in a particular sequence for hoisting.**
- 2. Articulating/knuckle-boom truck cranes that deliver material to a construction site when the crane is used to transfer building supply sheet goods or building supply packaged materials from the truck crane onto a structure, using a fork/cradle at the end of the boom, but only when the truck crane is equipped with a properly functioning automatic overload prevention device. Such sheet goods or packaged materials include, but are not limited to: sheets of sheet rock, sheets of plywood, bags of cement, sheets or packages of roofing shingles, and rolls of roofing felt.**

**Note:** The above articulating/knuckle-boom crane exclusion does not apply when it is used to 1) hold, support or stabilize the material to facilitate a construction activity, such as holding material in place while it is attached to the structure; 2) when the material being handled is a prefabricated component such as precast concrete members or panels, roof trusses, prefabricated building sections such as, but not limited to: floor panels, wall panels, roof panels, roof structures, or similar items; and, 3) when the material being handled by the crane is a structural steel member (for example, steel joists, beams, columns, steel decking (bundled or unbundled) or a component of a systems-engineered metal building.

**3. Other rigging requirements are found in the applicable provisions of Cranes and Derricks in Construction, found in Section III of this program, specifically, 1926.1401, 03, 04, 07, 08, 23, 27, 31, & 33.**

Prior to use on each shift, rigging equipment including slings and all fastenings and attachments will be inspected for damage or defects by a qualified person. Additional inspections will be performed during sling use and where service conditions warrant to ensure that it is safe.

Defective/damaged equipment including slings and rigging will not be used and will be immediately removed from service.

Per 1926.251(a)(3), rigging equipment, when not in use, will be removed from the immediate work area and stored properly so as not to present a hazard to employees.

Under no circumstances may any employee be under a suspended load.

29 CFR 1926.251, *Rigging Equipment for Material Handling*, contains Tables H-1 to H-20 which indicate rated capacities for various types of slings and grommets, safe working loads for shackles, number and spacing of U-Bolt Wire Rope Clips, and maximum allowable wear at any point of link.

Welded alloy steel chain slings must have permanently affixed durable identification stating size, grade, rated capacity, and sling manufacturer. Of course, hooks, rings, oblong links, pear-shaped links, welded or mechanical coupling links, or other attachments, when used with alloy steel chains, will have a rated capacity at least equal to that of the chain.

Rigging equipment will **not be loaded in excess** of its recommended safe working load and load identification will be attached to the rigging.

Specific requirements for use and inspection of alloy steel chains; wire rope; natural rope and synthetic fiber; synthetic webbing; and shackles are found in the above standards.

### **SCISSOR-LIFT FALL PROTECTION**

What type of fall protection is required for scissor-lifts? This apparently simple question has a relatively simple answer. However, how it is derived is somewhat complicated because OSHA does not have a standard to deal with this issue.

Clearly, there is a hazard -- falling from height -- however, fall protection while using a scissor-lift is not covered in the fall protection, scaffold and ladder fall protection, nor aerial lift fall protection standards.

Section 5(a)(1) of the Occupational Safety and Health Act, is a "catch all clause" which states: "Each employer shall furnish to each of its employees employment and a place of employment which are free from

recognized hazards that are causing or are likely to cause death or serious physical harm to his employees."

In the absence of a specific standard relating to a safety or health risk, the above is the reference OSHA will cite.

When assessing compliance efforts, OSHA considers the requirements of pertinent national consensus standards. In the case of scissor-lifts, ANSI/SIA A92.6-1990, *Self-propelled Elevated Work Platforms*, and ANSI/SIA A92.3, *Manually Propelled Elevating Aerial Platforms*, are used.

Fall protection is provided by employees maintaining firm footing on the lift and using guardrails. Under no circumstances are employees to place ladders or other items on the lift to extend their reach. Per ANSI/SIA standards, with which OSHA concurs, "Use of planks, ladders, or any other device on the aerial platform for achieving additional height or reach shall be prohibited." Use of these items negates the value of the guardrail system and may possibly exceed the scissor-lift's design limits for stability.

Further, personnel are not to tie off to items adjacent to the lift -- the most obvious reasons are: the anchorage point may not be sufficient and movement of the lift would pull the employee out of and off of the lift.

If, for some reason, guardrails are not being provided for a specific operational reason, then a personal fall protection system may be used which would include an anchorage point, lanyard and safety harness. However, this option is severely limited because its design would have to be approved by a registered engineer or the scissor-lift manufacturer would have to approve the use of the lift as an anchorage.

Under ideal conditions, rarely found on a construction site, scissor-lifts may be moved with the lift extended. However, should obstacles, debris, drop-offs, holes, depressions, ramps or other hazards be present, the lift must be lowered prior to movement.

Finally, if the employee leaves the safety of the scissor-lift platform while working at height, some sort of approved fall protection system must be employed.

## **SIGNS & TAGS**

### **Accident prevention signs and tags. - 1926.200**

When appropriate, signs and tags will be used to warn of specific hazards. Types of signs are classified according to their use, and their design is regulated by OSHA standard. All personnel will be instructed in the meaning of the various types of signs. Sign usage includes:

- a. Danger Signs (Red, Black & White): indicates immediate danger and denotes that special precautions are necessary.

- b. Caution Signs (Yellow Background): warns of a potential hazard or cautions against an unsafe practice.
- c. Safety Instruction Signs (White Background): used to provide general instructions and suggestions relative to safety measures.

The wording on signs must be positive, clear, concise, and easy to understand or the sign loses its value.

Accident prevention tags are to warn of hazardous or potentially hazardous conditions that are out of the ordinary, unexpected, or not readily apparent. They are not used where signs, guarding or other positive means of protection are used.

All tags must have:

- a. a signal word: “Danger”; “Caution”; “Warning”; BIOHAZARD (or its symbol) and a major message, and
- b. a major message such as: “High Voltage” or “Do not start”.  
[Major messages indicate the specific hazardous condition.]

The color scheme is basically the same as for signs:

red = danger  
yellow = caution  
orange = warning  
fluorescent orange = biological hazard.

- a. Danger Tags: indicate an immediate hazard that presents a threat of death or serious injury.
- b. Caution Tags: indicate a non-immediate hazard or unsafe practice that presents a lesser threat of injury.
- c. Warning Tags: indicate a hazard between “Danger” and “Caution”.
- d. BIOHAZARD Tags: indicate the actual or potential presence of a biological hazard and identify equipment, rooms, containers, etc., that may be contaminated.

Pay attention to signs and tags and realize that they are in place for only one reason -- your safety.

## **STAIRS**

### **Stairways. - 1926.1052**

Stairways that are not a permanent part of the structure on which construction work is being performed must have landings of at least 30 inches in the direction of travel and extend at least 22 inches in width at every 12 feet or less of vertical rise. Additionally,

- a. riser height and tread depth must be uniform within each flight of stairs.

- b. where doors or gates open directly on a stairway, a platform will be provided, and the swing of the door must not reduce the effective width of the platform to less than 20 inches.
- c. metal pan landings and metal pan treads, when used, must be secured in place before filling with concrete or other material.
- d. all parts of stairways will be free of hazardous projections, such as protruding nails.
- e. slippery conditions on stairways will be eliminated before use.
- f. except during stairway construction:
  - 1. foot traffic is prohibited on stairways with pan stairs where the treads and/or landings are to be filled at a later date, unless the stairs are temporarily fitted with solid material at least to the top edge of each pan. Temporary treads and landings will be replaced when worn below the level of the top edge of the pan.
  - 2. foot traffic is prohibited on skeleton metal stairs where permanent treads and/or landings are to be installed at a later date unless the stairs are fitted with secured temporary treads and landings long enough to cover the entire tread and/or landing area.

Treads for temporary service will be made of wood or other solid material and installed the full width and depth of the stair.

Stairways having four or more risers or rising more than 30 inches will be equipped with:

- a. at least one handrail; and
- b. one stairrail system along each unprotected side or edge.

### **TOOLS: HAND**

#### **General requirements. - 1926.300**

#### **Hand tools. - 1926.301**

Hand tools shall be used only for the purpose for which they are designed.

Hand tools will be kept clean and, where appropriate, oiled.

Hand tools which are damaged will not be used.

Hand held cutting tools will be kept sharp and will be sheathed or retracted when not in use.

When using a striking tool such as a hammer or chisel, safety glasses or safety goggles will be used.

Do not force tools.

If you are unfamiliar with the proper procedure for using a tool, ask your Supervisor for instruction.

Power tools may be operated only by those persons who are qualified by training or experience.

Do not alter guards on power tools; wear appropriate PPE.

Electrical tools must be grounded and, in the absence of permanent wiring, a Ground Fault Circuit Interrupter must be used.

Electric tools will not be lifted by their cords and pneumatic tools will not be lifted by their hoses.

### **TOOLS: PNEUMATIC POWERED**

**Eye and face protection. - 1926.102**

**General requirements. - 1926.300**

**Power-operated hand tools. - 1926.302**

Pneumatic powered tools must be safeguarded whenever there are hazardous employee exposures. This is especially important for point of operation guarding.

Three specific hazards associated with pneumatic powered tools which are unique to their use are noise levels, tool retention, and air hose pressure.

Care must be taken to assure that noise levels are within acceptable limits (noise monitoring may be necessary) and, if required, engineering controls and/or ear protection will be employed.

If there is a possibility of tool ejection during use, a tool retainer must be installed.

Safety will dictate that hose and hose connections be designed for the pressure and service to which they are subjected.

Eye protection will be worn when using pneumatic powered tools in accordance with the owner/operator's manual.

Compressed air will not be used for cleaning purposes except where pressure is reduced to less than 30 p.s.i. **and** effective chip guarding is in place **and** appropriate personal protective equipment is being worn. OSHA has determined that effective chip guarding means "any method or equipment which will prevent a chip or particle (of whatever size) from being blown into the eyes or skin of the operator or other workers in the area."

Care must be taken to ensure that employees are not exposed to unsafe levels of respirable dust or crystalline silica.

The PEL for particles not otherwise regulated is 5.0 mg/m<sup>3</sup>. The PEL for respirable dust containing crystalline silica is determined by the below formula:

PEL = 10 mg/m<sup>3</sup> ÷ (%SiO<sub>2</sub>+2), where %SiO<sub>2</sub>+2 refers to the amount of crystalline silica measured in the sample.

Our operations would not exceed these PEL's and respiratory protection is not required.

**TOOLS: POWDER-ACTUATED**  
**Eye and face protection. - 1926.102**  
**General requirements. - 1926.300**  
**Power-operated hand tools. - 1926.302**

A powder-actuated fastening tool propels a nail, pin, or fastener through an object to fasten it to another object. These tools, if misused, are extremely dangerous because essentially, they are similar to a pistol or rifle.

The speed of the projectile may range from 300 ft/second to 1290 ft/second.

Only trained and authorized persons may operate a powder actuated tool and, for safety, these tools should be kept secured when not in use.

Prior to use, the tool must be inspected and tested according to the manufacturer's instruction manual which should be kept with the tool.

Defective tools must not be used and they must be taken out of service.

Use of appropriate personal protective equipment - including, at least, eye/face and ear protection -- is required not only for the operator, but also those employees in the vicinity. PPE will be in accordance with the owner/operator's manual.

On the job site, each tool should be accompanied by: 1) its container; 2.) the operator's instruction & service manuals; 3) the tool inspection record; and 4) service tools & accessories.

Tools must not be loaded until just before firing and, under no circumstances, are they to be pointed at any person. Hands must be kept clear of the open barrel end. A powder activated tool must never be left unattended -- loaded or empty -- for safety and security reasons.

Fasteners must not be driven into very hard or brittle materials such as cast iron, glazed tile, surface-hardened steel, glass block, live rock, face brick or hollow tile; easily penetrated materials unless these materials are backed by a substance; nor a damaged area caused by an unsatisfactory fastening. Of course, these tools must never be used in an explosive or flammable atmosphere.



Before fastening questionable material, the operator can determine its suitability by using a fastener as a center punch. If the fastener point does not easily penetrate, is not blunted, and does not fracture the material, initial test fastenings will be made in accordance with the manufacturer's instructions.

The tool must be held perpendicular to the work surface and in the event of a misfire, the operator must hold the tool firmly against the work surface and follow, exactly, the manufacturer's instructions.

Tools must be used with the correct shield, guard, or attachments recommended by the manufacturer.

Because the case and load are color coded, it is imperative that the operator can distinguish the colors of brass and nickel as well as gray, brown, green, yellow and red and purple.

**VENTILATION**  
**Ventilation. - 1926.57**

There may be times in the course of our work such as grinding, cutting, sawing, sanding, etc. that hazardous dusts are released into the atmosphere that exceed the concentrations specified in the "Threshold Limit Values of Airborne Contaminants for 1970" of the American Conference of Governmental Industrial Hygienists, listed below:

<b>MINERAL DUSTS</b>	
<b>Substance</b>	<b>(a)mppcf</b>
SILICA Crystalline Quarts Threshold Limited calculated from the formula	$(b)(250) \div (\%SiO_2+5)$
Cristobalite. Amorphous, including natural diatomaceous earth	
SILICATES (Less than 1% crystalline silica)	
Mica	20
Portland Cement	20
Soapstone	20
Talc (non-abestiform)	20
Talc (fibrous), use asbestos limit	
GRAPHITE (Natural)	15
<b>INERT OR NUISANCE PARTICULATES</b> Note 1 Covers all organic and inorganic particulates not otherwise regulated. Same as Particulates Not Otherwise Regulated. Note 2 Inert or Nuisance Dusts includes all mineral, inorganic, and organic dusts as indicated by examples in TLV's Appendix D.	50 (or 15 mg/m <sup>3</sup> which-ever is the smaller) of total dust <1% SiO Note 1 See Table above

**a. Millions of particles per cubic foot or air, based on impinger samples counted by lightfield techniques.**

- b. The percentage of crystalline silica in the formula is the amount determined from airborne samples, except in those instances in which other methods have been shown to be applicable.

Below the above threshold limits, no action is required, however, employees may wear dust masks for personal comfort.

As always, engineering controls are preferred to personal protective equipment to deal with job site hazards. Therefore, local exhaust ventilation is a preferred method of maintaining atmospheres that have dust levels below the concentrations noted in the Dust Table, above.

Local exhaust ventilation must be designed so that they prevent dispersions of dust in concentrations causing harmful exposure and that dusts are not drawn through the work area of employees.

The dust collected by an exhaust or ventilating system will be discharged to the outside atmosphere.

If concentrations are so great that a dust separator is used, the dust and refuse will be disposed of in such a manner as to not harm employees. The exhaust will still be discharged to the outside atmosphere.

Of course, if the above ventilation procedures do not reduce the dust levels to acceptable limits, respirators will be used.

## **WELDING, CUTTING AND BRAZING**

General requirements. – 1910.252

Oxygen-fuel gas welding and cutting. 1910.253

Arc welding and cutting. – 1910.254

Gas welding and cutting. - 1926.350

Arc welding and cutting. - 1926.351

Fire prevention. - 1926.352

Ventilation and protection in welding, cutting, and heating. - 1926.353

Welding, cutting, and heating in way of preservative coatings. - 1926.354

Table Z-1. – Limits for Air Contaminants

Chromium (VI). – 1926-1126

Employees assigned to operate both arc welding and cutting and oxygen-fuel welding and/or brazing equipment, **and their supervisors**, must be properly trained and instructed in the operation of such equipment. Proper PPE will be worn by all welders.

Before welding or cutting, the supervisor or competent person will inspect the area with emphasis on fire prevention and authorize welding or cutting using our Hot Work Permit noting special precautions that must be taken.

An appropriate fire extinguisher and first aid equipment will be readily available for immediate use.

### Compressed Gas Cylinders Use:

Compressed gas cylinders are used on many job sites -- the most common being oxygen and acetylene for welding.

Failure to follow basic safety procedures could result in serious injuries such as:

- a. flash burn - due to explosion.
- b. fragment impalement - due to explosion.
- c. compression of the foot - due to mishandling of tanks.
- d. inhalation of hazardous gases - due to leakage.

Basic safety procedures for gas cylinder use:

- a. Cylinders must remain upright and chained to a substantial support or cart when in use.
- b. Wear appropriate personal protective equipment for the job -- such as steel toed shoes, apron, goggles, gloves, helmet, etc..
- c. Read and understand the MSDS for the gas being used and know the location of the MSDS in case of an emergency.
- d. Have appropriate fire extinguisher readily available.
- e. To release the gas, open the cylinder valve slowly -- standing away from the face and back of the gage -- and leave the opening tools in place (on the valve stem) for quick shut-off in the event of an emergency.
- f. Ensure cylinder valves, regulators, couplings, and hoses are free of oil and grease and ensure all connections are tight.
- g. When using oxygen-fuel systems, use flashback arrestors and reverse-flow check valves to prevent flashback.
- h. Keep cylinders away from open flames and sources of heat.
- i. **Cylinders are never allowed in confined spaces.**
  1. When welding or cutting in a confined space, the tanks must remain outside the confined space.
  2. Appropriate ventilation must be assured, portable equipment must be secured to prevent movement, if appropriate, a rescue plan should be prepared.
  3. If the rescue plan involves pulling the person out, attachment of the lifelines should be so the person's body does not jam in the exit and prevent his extraction.
  4. If arc welding is suspended for a substantial period of time, the electrodes must be removed to prevent accidental contact and the machine must be disconnected from the power source.

5. If gas cylinder work is suspended, the torch valves must be closed and the fuel-gas and oxygen supply must be positively shut off or disconnected outside the confined space.
  6. After welding operations are completed, the welder must mark the hot metal or provide some other means of warning other workers.
- j. Do not alter or attempt to repair safety devices or valves.
  - k. Remove the regulators when: a) moving cylinders; b) work is completed, and/or c) cylinders are empty.

Compressed gas cylinders will:

- a. have valve protectors in place when not in use or connected for use.
- b. be legibly marked to identify the gas contained therein.
- c. have the valves closed before the cylinder is moved, when the cylinder is empty, and at the completion of each job.
- d. be stored in areas away from intense heat, electric arcs, and high temperature lines.
- e. be secured upright (chained in portable dolly), in storage or transportation, to prevent tipping, falling, rolling, and damage from passing or falling objects. Oxygen cylinders must be kept 20 feet from any flammable gases or petroleum products.
- f. be marked "EMPTY" when appropriate.
- g. be removed from service if the regulators or gauges are defective.
- h. be used only for the purpose for which they are designed -- for example, cylinders will not be used as rollers or supports.
- i. be kept away from stairs.
- j. Workers in charge of oxygen or fuel-gas supply equipment (including distribution piping systems and generators) must be instructed and judged competent for such work.

Regulators and gauges will be inspected daily.

All cylinders, cylinder valves, couplings, regulators, hoses and apparatus will be kept free of oily or greasy substances.

Operators of welding equipment will report any equipment defect or safety hazards and discontinue use of equipment until its safety has been assured. Repairs will be made only by qualified personnel.

Persons performing arc welding and cutting must be properly instructed and qualified to operated such equipment and, if performing gas shielded

arc welding, must be familiar with Recommended Safe Practices for Gas-Shielded Arc Welding, A6.1-1966, American Welding Society, as well as 29 CFR 1910.252.

Electric welders will be inspected daily before use with emphasis on the cables. All splicing of cables must maintain the insulated protection with no exposed metal parts. Cables in need of repair will not be used.

The competent person will ensure that ventilation within a confined space is adequate to negate the possibility of a respiratory or explosion hazard.

A fire watch will be assigned when there is potential a fire might develop. Of course, any person assigned to fire watch must have received training in the specific fire extinguishing equipment being used. When welding, cutting, or brazing an object near a fire hazard that is not readily movable, the fire hazard will be removed. If any fire hazards remain, shields will be used to confine the sparks, heat, and slag. If the provisions of this paragraph cannot be met, welding and/or cutting **may not** take place. In fact, as a company policy, if welding cannot be conducted safely, it may not be conducted.

Fire watchers are required in all locations where other than a minor fire might develop and any of the below conditions exist:

- a. appreciable amounts of combustible materials closer than 35 feet to point of operation.
- b. appreciable combustibles are 35 feet or more away but are easily ignited by sparks.
- c. wall or floor openings within a 35 foot radius expose combustible material in adjacent areas including concealed spaces in walls or floors..
- e. Combustible materials are adjacent to the opposite side of metal partitions, ceilings, or roofs that are likely to be ignited by conduction or radiation.

The fire watch must be maintained at least one half hour after welding or cutting operations have ceased to detect, and extinguish, possible smoldering fires.

When performing operations capable of producing heat at chemical plants, refineries, or other facilities which have a higher degree of hazard than normal work sites, a hot work permit is generally required. Included in these types of operations are burning, cutting, heating, and welding.

With our Hot Work Permit are found fire safety instructions [(29 CFR 1910 252(a)] which must be read and understood by the persons identified on the permit

Welding, cutting, heating of metals of toxic significance (lead, zinc, cadmium, mercury, beryllium, or exotic metals or paints) in enclosed spaces will require

either general mechanical ventilation of sufficient capacity and so arranged as to produce the number of air changes necessary to maintain welding fumes and smoke within safe limits **or** local exhaust ventilation consisting of freely movable hoods intended to be placed by the welder or burner as close as practicable to the work. This system shall be of sufficient capacity and so arranged as to remove fumes and smoke at the source and keep the concentration of them in the breathing zone within safe limits.

This would include inert-gas metal-arc welding performed on stainless steel to protect against dangerous concentrations of nitrogen dioxide.

When performing welding operations on stainless steel and there is exposure to airborne chromium (VI) above its action level of 2.5 micrograms per cubic meter of air ( $2.5 \mu\text{g}/\text{m}^3$ ) calculated as an 8-hour time-weighted average (TWA), the provisions of 29 CFR 1926.1126 must be adhered to. The PEL is  $5 \mu\text{g}/\text{m}^3$ . If air monitoring, as described in 29 CFR 1926.1126 is below  $.5 \mu\text{g}/\text{m}^3$ , the provisions of this standard do not apply.

### **IDENTIFICATION OF HAZARDOUS JOB SITE MATERIALS**

The presence of asbestos, crystalline silica, lead, and even mercury is possible on many job sites. Before work begins, the appropriate PPE and respiratory protection requirements will be discussed with employees.

Because of the chronic (long term) nature of these hazards, detrimental health effects due to exposure would not be immediately noticed.

The competent person on site will prevent exposures to these materials.

Areas that contain the below materials will be cordoned off or protected with appropriate warning signs. Do not enter any restricted area unless dictated by job assignment and only after specific training for dealing with these hazards. The training would include PPE, respiratory protection, work procedures, medical surveillance, containment, hygiene, handling, testing, and labeling.

These materials may be “discovered” as work progresses and employees will be protected from these hazards by:

- a. identification of these items by the competent person.
- b. informing the owner, project designer, or engineer of the hazards.
- c. securing the area in question until testing proves samples to be negative.

Subcontractors who deal with these hazards will have specific programs that address the above issues.

## **ASBESTOS**

### **Substance Technical Information for Asbestos - Non-Mandatory - 1926.1101 App H**

Asbestos can be found in pipe, wall, and boiler insulation; exterior sheeting; and flooring. Friable or crumbling asbestos presents the most hazard as it can float in the air and be inhaled into the respiratory system. Without respiratory protection, the microscopic asbestos fibers can enter the deepest portion of the lung, causing scar tissue to develop and stiffen the lung. The net result is a reduction of gas exchange -- a condition called asbestosis. High levels of exposure to asbestos greatly increase one's chance of lung cancer.

## **CRYSTALLINE SILICA**

### **Silica, Crystalline (Respirable Size), National Institute of Health**

Crystalline Silica can be readily found on many job sites in rocks as well as many concrete and masonry products. Crystalline Silica can be released in the air when employees are performing such tasks as:

- a. chipping, hammering, drilling, crushing, or hauling rock.
- b. abrasive blasting.
- c. sawing, hammering, drilling, or sweeping concrete or masonry.

Unprotected respiratory exposure to crystalline silica may cause a lung disease called silicosis as well as cancer and death.

## **LEAD**

### **Substance Data Sheet for Occupational Exposure to Lead - 1926.62 App A**

Lead can be found in water pipes, soldering, and paint. Lead is a heavy, toxic metal which can be absorbed into your body by ingestion and/or inhalation. It is a cumulative poison which can stay in your body for decades.

While massive doses of lead can kill in a matter of days, the more likely scenario on a job site is moderate exposure to asbestos or lead which probably would not create any health problems for years -- if at all.

## OSHA COMPLIANCE PROGRAMS

When you are confronted by situations listed below, you must perform your tasks in accordance with our written programs which comply with specific OSHA standards. Below is an overview of each program.

### Control of Hazardous Energy

Control of hazardous energy (lockout/tagout) procedures apply when there is a possibility of injury due to the unexpected energization, start up or release of stored energy while constructing, installing, setting up, adjusting, inspecting, modifying, maintaining or servicing fixed machinery.

Lockout/Tagout is not required for work on cord and plug connected electric equipment for which exposure to hazards can be controlled by unplugging equipment nor to hot tap operations.

Failure to follow lockout/tagout procedures may result in being crushed, dismembered, mangled, paralyzed, electrocuted, sliced, or punctured by the sudden release of energy from the following types of sources: capacitor; chemical, counter weight, electrical, engine, flywheel, hydraulic, pneumatic, spring, thermal, or gravity.

#### Procedures

- Preparation for Shutdown: Using the Energy Source Evaluation, all isolating devices must be located.
- Equipment Shutdown: Inform the affected person and use normal shut down procedures.
- Equipment Isolation: Physically isolate the equipment from its energy source(s) -- there may be more than one.
- Device application: Apply color coded locks and/or tags to hold the isolating devices in a "Neutral" or "Off" position.
- Release of Stored Energy: Dissipate stored energy.
- Verification of Isolation: Prior to work, operate machine controls and ensure the machine will not operate.
- Release from Lockout/Tagout: The person who applied the devices is the one who removes them after ensuring the area is clear and affected employees are informed.

Authorized employees will lockout/tagout the energy isolating devices with assigned individual locks. Locks or other lockout/tagout devices will be used for no other purpose, will be color coded, and will indicate the identity of the



authorized employee applying the device. A lock can be used without a tag if only one circuit or piece of equipment is being deenergized, the lockout period does not extend beyond the work shift, and employees are aware that a tag is not being used with the lock.

A tag may be used alone if it provides full employee protection and is used with another safety measure. Other safety measures include the removal of an isolating circuit element, the blocking of a controlling switch, or the opening of an extra disconnecting device. Tags must warn against the hazardous conditions if the machine or equipment is energized and shall include a legend like the following: *Do Not Start; Do Not Open; Do Not Close; Do Not Operate; etc..*

All stored energy must be isolated. Should there be a possibility of re-accumulation of stored energy, verification of isolation must be continued until servicing is complete. The authorized employee shall operate the normal operating controls to verify that the machine or equipment has been deenergized and that it will not operate. After the above test, the operating controls will be returned to the "Neutral" or "Off" position.

Before the lockout/tagout devices are removed and energy is restored: the work area will be inspected to ensure the nonessential items have been removed and the machine or equipment components are operationally intact; the work area will be checked to ensure all employees have been positioned safely or removed. A device can only be removed by the one who applied it unless that person is not available. Another competent person may remove the device as long as the employee who applied it is informed.

If service and maintenance require more than one individual, one person will be designated as Group Leader and will maintain overall responsibility for employees working under him/her.

Lockout/tagout procedures extending into a second shift:

- a. If the energy isolation device will accept two lockout/tagout devices, the authorized employee coming on duty will put his device in place before the employee going off duty removes his device.
- b. If the energy isolation device will not accept two devices, the incoming and outgoing authorized employees will notify affected employees that a lockout/tagout change is taking place; both employees will insure the surrounding area is free of tools and employees; the outgoing employee will remove his device and the incoming employee will install his; finally, the incoming employee will notify affected employees the change is completed.

## **Exposure Control Plan**

(for bloodborne pathogens or other infectious materials)

An exposure control plan is required when emergency medical response is not available within a reasonable time frame and personnel are assigned as first aid providers as an additional duty.

The primary hazard relates to the possibility of infection resulting from exposure to blood-borne pathogens or other infectious materials while providing first aid to a trauma victim or cleaning up bodily fluids after an incident.

As a statement of policy, should an exposure control plan be required, Universal Precautions will be used. Essentially, this means that each trauma victim's blood, bodily fluids, and other potentially infectious materials will be treated as if they are known to be infectious.

First aid providers must understand:

- a. the hazards of bloodborne pathogens and other infectious materials.
- b. engineering & work practice controls designed to minimize possible exposure such as:
  1. handwashing equipment & procedures.
  2. eating; drinking & smoking prohibitions.
  3. the containment of contaminated sharps.
  4. the containment of other regulated waste.
  5. the disposal of contaminated sharps & regulated waste
  6. controlling splashing/spraying of potentially infectious materials.
  7. the prohibition of mouth pipetting (the mouth suction of blood through a tube).
- c. the need to place an impermeable barrier between potential infectious materials and the provider's work clothes, street clothes, undergarments, skin, eyes, mouth, or other mucous membranes using:
  1. disposable gloves
  2. utility gloves
  3. eye & respiratory protection
  4. protective body clothing
- d. hepatitis B epidemiology and how bloodborne pathogens are transmitted.

- e. the importance of hepatitis B vaccination within 24 hours of possible exposure.
- f. the procedure for incident report preparation and the importance of completing them, in writing, before the end of the work shift.

### **Fall Protection**

Fall protection is required for employees working six feet or more above walking/working surface, when there is a potential for objects to fall on them, or when they are working around covers.

The obvious hazard is falling or being hit by a falling object.

A fall protection plan is required when conventional fall protection systems are infeasible.

Through training, employees must know where conventional fall protection systems are required such as when working on or around:

1. unprotected sides and edges
2. leading edges
3. hoist areas
4. holes
5. formwork & reinforcing steel
6. ramps, runways & other walkways.
7. excavations
8. dangerous equipment
9. overhand bricklaying & related work
10. roofing work on low-sloped roofs
11. steep roofs
12. precast concrete erection
13. residential construction
14. wall openings

Additionally, employees must understand:

- a. the selection, use, and maintenance of fall protection system(s).
- b. the types of fall protection systems:
  1. guardrail system
  2. personal fall arrest system
  3. safety net system

4. warning line system
5. safety monitoring system
6. positioning device system
7. controlled access zone (CAZ)
8. covers
9. protection from falling objects.

### **Forklifts**

Forklifts include: fork trucks; tractors; platform lift trucks; motorized hand trucks; and other specialized industrial trucks powered by electric motors or internal combustion engines.

The primary hazards involved in truck operation are:

1. physically hitting a person/object with the truck or load.
2. having a load fall and hit the operator or other person.
3. having the truck tip and crush the operator or other person.
4. fire or explosion during refueling/recharging.

Supervisors should ensure that truck operators are authorized by the Program Administrator. Authority to operate a truck will be revoked if unsafe acts are observed or it is apparent that the operator has not retained the knowledge and job skills necessary to safely perform truck operations.

Supervisors should caution employees not involved with truck operations to stay clear of them due to limited visibility of the operator and the size and weight of the vehicle and load.

### **Hazard Communication**

Practically all chemical products have physical or health hazards if they are inadvertently spilled or improperly used. Our Hazard Communication Plan details the methods used to keep our employees informed of these potential hazards.

The Program Administrator will ensure that all personnel understand:

- a. the importance and use of labels; material safety data sheets (MSDS); and the ready accessibility of MSDS.
- b. the physical & health hazards of chemicals used in the workplace.
- c. the methods used to detect the release of a hazardous chemical.

- d. the methods to protect oneself from chemical hazards including PPE; work practices; & emergency procedures.
- e. the need to share product information with other contractors.

### **Hearing Conservation**

Supervisors are to ensure that employees are not exposed to occupational noises that exceed the levels listed below. Excessive noise may cause permanent hearing loss. Supervisors should be aware that hearing loss is often painless and unnoticeable.

#### Permissible Noise Exposures

<u>Sound level</u>	<u>Duration per day, hours</u>	<u>dBA slow response</u>
	8	90
	6	92
	4	95
	3	97
	2	100
	1 1/2	102
	1	105
	1/2	110
	1/4 or less	115

The Program Administrator will ensure that applicable standards are posted, medical surveillance and noise monitoring are instituted, and that all affected personnel understand the process of hearing and the importance of preventing hearing loss.

### **Permit-Required Confined Space**

Permit-required confined spaces may present a very hazardous environment if specific procedures, testing, and training are not implemented prior to entry. As a reminder:

A confined space is a space that:

- is large enough and so configured that an employee can bodily enter and perform assigned work; and

- has limited or restricted means for entry or exit. These spaces may include: ventilation or exhaust ducts, bins and tanks, boilers, sewers, tunnels and open top spaces more that 4 feet in depth such as pits, tubs, and vessels; and

- is not designed for continuous employee occupancy.

A permit-required confined space is:

a confined space that contains any recognized serious safety or health hazards. These hazards may be: engulfment by materials; entrapment by space shape; inhalation of hazardous (possibly fatal) atmospheres.

Supervisors should ensure that employees understand:

1. the need to identify and evaluate permit space hazards before entry.
2. the need to test conditions before entry and monitor conditions during entry.
3. how to prevent unauthorized entry.
4. how to eliminated or control hazards for safe permit-space entry operations.
5. the need to ensure that at least one attendant is stationed outside the permit-required space for the duration of the entry operations.
6. how to coordinate and monitor entry operations when we are working with employees of another contractor or client within a permit-required confined space.
7. our procedures for emergency rescue.
8. the establishment of a written procedure for preparation, issuance, use, and cancellation of entry permits.

### **Personal Protective Equipment**

A hazard assessment will be made on all job sites to determine what types of personal protective equipment (PPE) are appropriate. A major part of this hazard assessment will be determining what PPE needs can be eliminated through feasible engineering controls or work procedures.

Types of hazard categories that are considered are: impact; penetration; compression; chemical; heat; harmful dust; and light radiation.

The focus of PPE is to eliminate eye, hand, foot, limb, and head injury. Visitors exposed to the identified hazards will be loaned appropriate PPE (and given instruction in its use) prior to hazard exposure.

You must understand the limitations of your PPE; the correct procedure for putting on, adjusting, and removing the PPE; and the proper care, maintenance, and useful life of the PPE.

Cleanliness of PPE is of importance particularly when dealing with eye protection where fogging, scratches, or dirt can render the PPE a hazard rather than protection from a hazard.

Unique PPE required for job performance such as hard hats, respirators, ear plugs, safety goggles, etc. will be supplied to the employees. They are responsible for maintenance of the equipment issued to them. Items of PPE that are damaged or non-functioning should be turned in for repair or replacement.

For personal comfort and to eliminate nuisance noises and nuisance respiratory conditions that are not at or above the threshold level for required protection, dust masks and ear plugs may be used at any time.

### **Respiratory Protection**

As a supervisor, it is extremely important that you do not allow employees to be exposed to atmospheres that do not contain clean, breathable air free from contaminants that exceed permissible exposure limits.

Respiratory hazards can range from mildly irritating to fatal.

Because of the serious consequences of improperly using respiratory protection, those for whom it applies, must understand:

1. the importance of medical approval for respiratory use.
2. the respirator selection process.
3. how to determine the service life of particulate filters.
4. fit testing.
5. user seal tests.
6. the importance of work area surveillance.
7. cleaning, inspection & maintenance of respirators.

Of course, job sites often contain nuisance dusts that do not exceed permissible exposure limits. In these cases, employees may wear dust masks for personal comfort. Supervisors should caution those wearing dust masks that they do not offer true respiratory protection.

### **Scaffolds & Ladders**

Scaffold and ladder accidents are often quick and devastating. The primary hazards are: falls, electrical shock, and being hit by falling objects.

On the job site, supervisors must ensure that employees are:

1. following established procedures for dealing with the above hazards.
2. properly using both scaffolds and ladders
3. not exceeding the load and the load-carrying capacities of the scaffolds and ladders.

During routine job site inspections, supervisors should be constantly vigilant for violations of the below ladder safety rules and take immediate corrective action to ensure the safety of our employees:

- a. a stairway or a ladder will be provided at all personnel points of access where there is a break in elevation of 19 inches or more.
- b. ladders will never be overloaded.
- c. ladder rungs, cleats, and steps must be parallel, level, and uniformly spaced when a ladder is in position for use.
- d. ladders will not be tied or fastened together unless they are so designed.
- e. portable ladders used for gaining access to an upper level will extend at least 3 feet above the upper landing surface or the ladder will be secured at its top.
- f. ladders must be free of oil, grease, or other slipping hazards.
- g. ladders must be used for the purpose for which they were designed.
- h. non-self supporting ladders will be used at an angle that the horizontal distance from the top support to the foot of the ladder is approximately  $\frac{1}{4}$  of the working length of the ladder.
- i. ladders will only be used on stable and level surfaces unless secured to prevent displacement.
- j. ladders shall not be used on slippery surfaces unless secured or provided with slip-resistant feet to prevent accidental displacement.
- k. ladders placed in any location where they can be displaced by workplace activities or traffic will be secured to prevent accidental displacement, or a barricade will be used to keep the activities or traffic away from the ladder.
- l. the area around the top and bottom of the ladder shall be kept clear.
- m. ladders shall not be moved, shifted, or extended while occupied.
- n. the top step of a stepladder shall not be used as a step.
- o. portable ladders with structural defects will be immediately marked in a manner that readily identifies them as defective and removed from service.
- p. when ascending or descending a ladder, one must face the ladder.
- q. employees must use at least one hand to grasp the ladder when progressing up and/or down the ladder.
- r. employees are not to carry any object or load that could cause loss of balance and a resultant fall.



# Project Emergency Phone Numbers



## **Designation of Competent Person(s)**

**Framing Authority**  
Independence Village

**DESIGNATION OF COMPETENT PERSON(S)**

Each individual listed below, by virtue of training and/or experience, is designated a “Competent Person” as that designation relates to the area of expertise noted.

A competent person is one who is capable of identifying existing and predictable hazards in the surrounding or working conditions which are unsanitary, hazardous, or dangerous to employees, and who has authorization to take prompt corrective measures to eliminate them.

Kurt Foster  
(Name)

Osha Safety Standards  
(Area of Expertise)

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_  
Florin Maidaniuc  
Safety Director

# **Job Site Checklist**

## **General** **Scaffolds**

Framing Authority  
Independence Village

**JOB SITE CHECKLIST**  
[General]

Job Site Identification: \_\_\_\_\_

Date: \_\_\_\_\_

\_\_\_\_\_  
(Signature of Competent Person)

Check appropriate box:

Yes No NA

Postings

- |   |                          |                          |                          |
|---|--------------------------|--------------------------|--------------------------|
| a. OSHA Form 3165   | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| b. OSHA Form 300A (February 1 to April 30)                                  | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| c. Emergency Phone Numbers<br>(Hospital - Emergency Response - Main Office) | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |

Administrative

- |  |                          |                          |                          |
|--|--------------------------|--------------------------|--------------------------|
| a. MSDS readily accessible                     | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| b. Hazard communication information "shared"   | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| c. Fire extinguishers accessible and inspected | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| d. Employees appropriately trained             | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |

Job Site

- |   |                          |                          |                          |
|---|--------------------------|--------------------------|--------------------------|
| a. First aid kits available and stocked         | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| b. General housekeeping                         | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| c. Adequate restrooms facilities                | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| d. Potable water available                      | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| e. Warning signs, tags, barricade tape in place | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |

Temporary Electrical Wiring

- |   |                          |                          |                          |
|---|--------------------------|--------------------------|--------------------------|
| a. Extension cords inspected & free of defects            | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| b. Ground fault circuit interrupters (GFCI) in use        | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| c. All equipment properly grounded                        | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| d. Temporary wiring clear of employee & vehicular traffic | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |

Personal Protective Equipment (PPE) Required

(Note: Serviceable equipment available & training received)

- |                                      |                          |                          |                          |
|--------------------------------------|--------------------------|--------------------------|--------------------------|
| a. Hard Hats                         | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| b. Eye protection                    | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| c. Appropriate, approved, work shoes | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| d. Hearing protection                | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| e. Gloves                            | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |

<u>Equipment including PPE, Ladders &amp; Scaffolds &amp; Tools</u>	<u>Yes</u>	<u>No</u>	<u>NA</u>
a. Inspected before use	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
b. Defective items tagged and removed from service	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
c. Powered Equipment operators trained and authorized	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Ladders

- |  |                          |                          |                          |
|--|--------------------------|--------------------------|--------------------------|
| a. Side rails extend at least 3' above upper landing surface | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| b. Ladders tied-off to prevent displacement                  | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |

Scaffolds

- |  |                          |                          |                          |
|--|--------------------------|--------------------------|--------------------------|
| a. Guard rails, full planking, bracing & ladder access | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
|--|--------------------------|--------------------------|--------------------------|

Fall Protection

- |   |                          |                          |                          |
|---|--------------------------|--------------------------|--------------------------|
| a. Personnel trained in fall protection   | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| b. Conventional Fall Protection System Used   | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| 1. Guardrail System   | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| 2. Personal Fall Arrest System  | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| 3. Warning Line System  | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| 4. Controlled Access Zone System  | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| 5. Safety Monitoring System: Monitor must be a competent to recognize fall hazards & know the responsibilities of the position. | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| d. Fall Protection Plan used: 29 CFR 1926.502(k); is on site.   | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |

Other

- |          |                          |                          |                          |
|----------|--------------------------|--------------------------|--------------------------|
| a. _____ | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| b. _____ | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| c. _____ | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |

Safety Enforcement

Unsafe work practices will be corrected immediately upon discovery and if total job site safety cannot be restored, job will be shut down until corrections are made. The below listed persons were working in an unsafe manner & enforcement documentation is or will be prepared at the earliest opportunity consistent with safety.

\_\_\_\_\_  
(Name)

\_\_\_\_\_  
(Unsafe Act & Corrective Measure)

\_\_\_\_\_

\_\_\_\_\_  
(Name)

\_\_\_\_\_  
(Unsafe Act & Corrective Measure)

\_\_\_\_\_

Framing Authority  
Independence Village

**JOB SITE CHECKLIST**  
[Scaffolds]

Job Site Identification: \_\_\_\_\_

Date: \_\_\_\_\_

\_\_\_\_\_  
(Signature of Competent Person)

Check appropriate box:

Yes No NA

**Erection & Dismantling**

1. Only trained, competent persons involved
2. \*Daily assessment: need for & feasibility of fall protection    
\* During the complete time frame of scaffold erection and/or dismantling,  
this daily assessment must be made and this checklist signed and dated.
  - a. fall protection feasible
3. Hard hats always worn
4. Other PPE as appropriate, i.e., steel toed boots, gloves,  
eye protection
5. Supported scaffold poles, legs, posts, frames, and uprights  
resting on base plates **and** mud sills or other adequate  
firm foundation
6. Frames, legs, braces: plumb, level and secure
7. Locking pins: in place and secure
8. Cleated planks used or planks extend at least 6 inches  
and not more than 12 inches over support
9. Planks over 10 feet in length will not extend more  
than 18 inches over support
10. No more than one (1) inch space between platforms units  
as well as uprights
11. Supported scaffolds with height to base width greater than  
4:1 restrained by guying, tying, bracing, or equivalent means
12. Safe distance from power lines:     
**Insulated lines**
  - a. Less than 300 Volts 3 feet
  - b. 300 Volts to 50 kv: 10 feet
  - c. More than 50 kv: 10 feet plus 0.4 inches for each 1 kv over 50 kv**Uninsulated lines**
  - a. Less than 50 kv: 10 Feet
  - b. More than 50 kv: 10 feet plus 0.4 inches for each 1 kv over 50 kv
13. Above ten (10) feet, installation of guard rails, mid rails  
toe boards



Check appropriate box:

Yes No NA

14. Guardrail systems [on all \*open sides and ends] installed before scaffold released for employee use    
\*An open side is greater than 14 inches from the face of the work except:  
1) For plastering and lathing it is greater than 18 inches from the face of the work.  
2) For outrigger scaffolding it is 3 inches from the face of the work.
15. Above two (2) feet, access provided (stairs, ladder, ramp)
16. Components inspected; defective items removed from site
17. If appropriate, warning signs, barricade tape in place
18. Temporary wiring clear of employee & vehicular traffic

**Scaffold Use**

1. Daily inspection by competent person
2. Only trained employees allowed on scaffold
3. Hard hats always worn
4. Other PPE as appropriate, i.e., steel toed boots, gloves, eye protection
5. Employees will not stand on guardrails or midrails or cross rails
6. Employees will not stand on boxes or step ladders to gain height
7. Potential falling objects, too large to be contained by toe-boards, mess, etc. will be placed away from edge
8. Scaffolds will not be loaded above their capacity. Under no circumstances will platforms deflect more than 1/60 the span when loaded.

**Other**

- a. \_\_\_\_\_
- b. \_\_\_\_\_
- c. \_\_\_\_\_

**Safety Enforcement**

Unsafe work practices will be corrected immediately upon discovery and if total job site safety cannot be restored, job will be shut down until corrections are made. The below listed person was working in an unsafe manner & enforcement documentation is or will be prepared at the earliest opportunity consistent with safety.

\_\_\_\_\_  
(Name)

\_\_\_\_\_  
(Unsafe Act & Corrective Measure)

\_\_\_\_\_  
(Date)

\_\_\_\_\_  
(Signature of Supervisor/Competent Person)

# Enforcement Documentation

**Framing Authority**  
Independence Village

**ENFORCEMENT DOCUMENTATION**

Date: \_\_\_\_\_ Check One:  Minor  Major  Willful

Employee Name: \_\_\_\_\_

Supervisor: \_\_\_\_\_

Description of violation: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Possible Adverse Consequences: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Corrective Action: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Employee Acknowledgment:

\_\_\_\_\_  
(Employee Signature) (Date)

Employee statement/rebuttal (optional): \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

**Witnesses:** (if appropriate & available. An effort should be made to obtain witnesses for willful safety violations)

\_\_\_\_\_  
(Print name) (Signature)

\_\_\_\_\_  
(Print name) (Signature)

Note: With the exception of willful violations, this form will be destroyed after a 12 month period.

# Hot Work Permit

Framing Authority  
Independence Village

**Hot Work Permit**

This form provides written authorization for the below listed individual(s) to perform operations capable of providing a source of ignition.

Object on which hot work is to be performed: \_\_\_\_\_

Date(s) hot work is to be performed: \_\_\_\_\_  
(From) (To)

Hot work is applicable to the below listed type of operation:

(Check appropriate box)

- Burning
- Cutting
- Heating
- Riveting
- Welding
- Other: \_\_\_\_\_

Persons performing hot work operations:

_____ (Name)	_____ (SSN or Employee ID No.)
_____	_____
_____	_____
_____	_____
_____	_____
_____	_____

The above persons have been provided with a copy of **29 CFR 1910.252(a)** [see **following page**] and its provisions will be complied with.

A copy of this Hot Work Permit will remain on file until the completion of the hot work operation listed above.

\_\_\_\_\_  
(Facility) (Date)

\_\_\_\_\_  
(Signature of Person Authorized to Issue Hot Work Permit) (Title)

## 29 CFR 1910.252(a)

### Title: Fire prevention and protection

(a) **Fire prevention and protection** - (1) Basic precautions. For elaboration of these basic precautions and of the special precautions of paragraph (d)(2) of this section as well as a delineation of the fire protection and prevention responsibilities of welders and cutters, their supervisors (including outside contractors) and those in management on whose property cutting and welding is to be performed, see, Standard for Fire Prevention in Use of Cutting and Welding Processes, NFPA Standard 51B, 1962. The basic precautions for fire prevention in welding or cutting work are:

(i) Fire hazards. If the object to be welded or cut cannot readily be moved, all movable fire hazards in the vicinity shall be taken to a safe place.

(ii) Guards. If the object to be welded or cut cannot be moved and if all the fire hazards cannot be removed, then guards shall be used to confine the heat, sparks, and slag, and to protect the immovable fire hazards.

(iii) Restrictions. If the requirements stated in paragraphs (a)(1)(i) and (a)(1)(ii) of this section cannot be followed then welding and cutting shall not be performed.

(2) Special precautions. When the nature of the work to be performed falls within the scope of paragraph (a)(1)(ii) of this section certain additional precautions may be necessary:

(i) Combustible material. Wherever there are floor openings or cracks in the flooring that cannot be closed, precautions shall be taken so that no readily combustible materials on the floor below will be exposed to sparks which might drop through the floor. The same precautions shall be observed with regard to cracks or holes in walls, open doorways and open or broken windows.

(ii) Fire extinguishers. Suitable fire extinguishing equipment shall be maintained in a state of readiness for instant use. Such equipment may consist of pails of water, buckets of sand, hose or portable extinguishers depending upon the nature and quantity of the combustible material exposed.

(iii) Fire watch. (A) Fire watchers shall be required whenever welding or cutting is performed in locations where other than a minor fire might develop, or any of the following conditions exist:

{1} Appreciable combustible material, in building construction or contents, closer than 35 feet (10.7 m) to the point of operation.

{2} Appreciable combustibles are more than 35 feet (10.7 m) away but are easily ignited by sparks.

{3} Wall or floor openings within a 35-foot (10.7 m) radius expose combustible material in adjacent areas including concealed spaces in walls or floors.

{4} Combustible materials are adjacent to the opposite side of metal partitions, walls, ceilings, or roofs and are likely to be ignited by conduction or radiation.

(B) Fire watchers shall have fire extinguishing equipment readily available and be trained in its use. They shall be familiar with facilities for sounding an alarm in the event of a fire. They shall watch for fires in all exposed areas, try to extinguish them only when obviously within the capacity of the equipment available, or otherwise sound the alarm. A fire watch shall be maintained for at least a half hour after completion of welding or cutting operations to detect and extinguish possible smoldering fires.

(iv) Authorization. Before cutting or welding is permitted, the area shall be inspected by the individual responsible for authorizing cutting and welding operations. He shall designate precautions to be followed in granting authorization to proceed preferably in the form of a written permit.

(v) Floors. Where combustible materials such as paper clippings, wood shavings, or textile fibers are on the floor, the floor shall be swept clean for a radius of 35 feet (10.7 m). Combustible floors shall be kept wet, covered with damp sand, or protected by fire-resistant shields. Where floors have been wet down, personnel operating arc welding or cutting equipment shall be protected from possible shock.

(vi) Prohibited areas. Cutting or welding shall not be permitted in the following situations:

(A) In areas not authorized by management.

(B) In sprinklered buildings while such protection is impaired.

(C) In the presence of explosive atmospheres (mixtures of flammable gases, vapors, liquids, or dusts with air), or explosive atmospheres that may develop inside uncleaned or improperly prepared tanks or equipment which have previously contained such materials, or that may develop in areas with an accumulation of combustible dusts.

(D) In areas near the storage of large quantities of exposed, readily ignitable materials such as bulk sulfur, baled paper, or cotton.

(vii) Relocation of combustibles. Where practicable, all combustibles shall be relocated at least 35 feet (10.7 m) from the work site. Where relocation is impracticable, combustibles shall be protected with flameproofed covers or otherwise shielded with metal or asbestos guards or curtains.

(viii) Ducts. Ducts and conveyor systems that might carry sparks to distant combustibles shall be suitably protected or shut down.

(ix) Combustible walls. Where cutting or welding is done near walls, partitions, ceiling or roof of combustible construction, fire-resistant shields or guards shall be provided to prevent ignition.

(x) Noncombustible walls. If welding is to be done on a metal wall, partition, ceiling or roof, precautions shall be taken to prevent ignition of combustibles on the other side, due to conduction or radiation, preferably by relocating combustibles. Where combustibles are not relocated, a fire watch on the opposite side from the work shall be provided.

(xi) Combustible cover. Welding shall not be attempted on a metal partition, wall, ceiling or roof having a combustible covering nor on walls or partitions of combustible sandwich-type panel construction.

(xii) Pipes. Cutting or welding on pipes or other metal in contact with combustible walls, partitions, ceilings or roofs shall not be undertaken if the work is close enough to cause ignition by conduction.

(xiii) Management. Management shall recognize its responsibility for the safe usage of cutting and welding equipment on its property and:

(A) Based on fire potentials of plant facilities, establish areas for cutting and welding, and establish procedures for cutting and welding, in other areas.

(B) Designate an individual responsible for authorizing cutting and welding operations in areas not specifically designed for such processes.

(C) Insist that cutters or welders and their supervisors are suitably trained in the safe operation of their equipment and the safe use of the process.

(D) Advise all contractors about flammable materials or hazardous conditions of which they may not be aware.

(xiv) Supervisor. The Supervisor:

(A) Shall be responsible for the safe handling of the cutting or welding equipment and the safe use of the cutting or welding process.

(B) Shall determine the combustible materials and hazardous areas present or likely to be present in the work location.

(C) Shall protect combustibles from ignition by the following:

{1} Have the work moved to a location free from dangerous combustibles.

{2} If the work cannot be moved, have the combustibles moved to a safe distance from the work or have the combustibles properly shielded against ignition.

{3} See that cutting and welding are so scheduled that plant operations that might expose combustibles to ignition are not started during cutting or welding.

(D) Shall secure authorization for the cutting or welding operations from the designated management representative.

(E) Shall determine that the cutter or welder secures his approval that conditions are safe before going ahead.

(F) Shall determine that fire protection and extinguishing equipment are properly located at the site.

(G) Where fire watches are required, he shall see that they are available at the site.

(xv) Fire prevention precautions. Cutting or welding shall be permitted only in areas that are or have been made fire safe. When work cannot be moved practically, as in most construction work, the area shall be made safe by removing combustibles or protecting combustibles from ignition sources.

(3) Welding or cutting containers - (i) Used containers. No welding, cutting, or other hot work shall be performed on used drums, barrels, tanks or other containers until they have been cleaned so thoroughly as to make absolutely certain that there are no flammable materials present or any substances such as greases, tars, acids, or other materials which when subjected to heat, might produce flammable or toxic vapors. Any pipe lines or connections to the drum or vessel shall be disconnected or blanked.

(ii) Venting and purging. All hollow spaces, cavities or containers shall be vented to permit the escape of air or gases before preheating, cutting or welding. Purging with inert gas is recommended.

(4) Confined spaces - (i) Accidental contact. When arc welding is to be suspended for any substantial period of time, such as during lunch or overnight, all electrodes shall be removed from the holders and the holders carefully located so that accidental contact cannot occur and the machine be disconnected from the power source.

(ii) Torch valve. In order to eliminate the possibility of gas escaping through leaks or improperly closed valves, when gas welding or cutting, the torch valves shall be closed and the gas supply to the torch positively shut off at some point outside the confined area whenever the torch is not to be used for a substantial period of time, such as during lunch hour or overnight. Where practicable, the torch and hose shall also be removed from the confined space.

# Hand Signals for Cranes

**U.S. Department of Labor  
 Mine Safety and Health Administration  
 Hand Signals for Lifting Equipment.**

**Know Your Hand Signals!**

**Basic Standard Hand Signals for Cranes and Hoisting Equipment**



**HOIST:** With forearm vertical, and forefinger pointing up, move hand in small horizontal circle.



**LOWER:** With arm extended downward, forefinger pointing down, move hand in a small horizontal circle.



**RAISE BOOM:** Arm extended, fingers closed, thumb pointing upward.



**LOWER BOOM:** Arm extended, fingers closed, thumb pointing downward.



**EXTEND BOOM:** Both fists in front of body with thumbs pointing outward.



**RETRACT BOOM:** Both fists in front of body with thumbs pointing toward each other.




**SWING:** Arm extended, point with finger in direction of desired boom swing.



**STOP DOG EVERYTHING:** Clasp hands in front of body.



**MOVE SLOWLY:** Use one hand to give any motion signal and place the other hand motionless in front of the hand giving the signal.



**TRAVEL:** Arm extended forward, hand open and slightly raised, make pushing motion in direction of travel.



**USE MAIN HOIST:** Tap fist on head; then use regular signals.



**USE WHIP LINE (AUXILIARY HOIST):** Tap elbow with one hand; then use regular signals.



**STOP:** Arm extended, palm down, move arm back and forth horizontally.



**RAISE THE BOOM AND LOWER THE LOAD:** With arm extended, thumb pointing up, flex fingers in and out as long as load movement is desired.



**LOWER THE BOOM AND RAISE THE LOAD:** With arm extended, thumb pointing down, flex fingers in and out as long as load movement is desired.



**EMERGENCY STOP:** Both arms extended, palms down, move arms back and forth horizontally.

Issued:  
 Tag # AP2003-M061



# Forklift Checklist

# Framing Authority Independence Village

## FORKLIFT CHECK LIST

VEHICLE TYPE: \_\_\_\_\_

DATE: \_\_\_\_\_

VEHICLE NUMBER: \_\_\_\_\_

OPERATOR NAME: \_\_\_\_\_

VISUAL INSPECTION	Mon	Tues	Wed	Thurs	Fri	Sat.	Sun
Overall vehicle condition							
Operators manual							
Fire extinguisher							
Head lights							
Tail lights							
Signal lights							
Warning lights							
Seat							
Seat belt							
Tires, wheels, rims							
Overhead cage protection							
Forks							
Mast							
Mast chains							
Mast tilt							
Hydraulic lines							
Wires							
Cosmetic Damage: Explain:							
<b>FLUIDS (check leakage &amp; )</b>							
Brake fluid							
Engine oil							
Fuel							
Hydraulic fluid							
Coolant							
<b>VEHICLE OPERATIONS</b>							
Starter							
Gauges: Battery							
Oil pressure							
Temperature							
Hour meter							
Seat safety switch							
Backup warning device							
Warning light							
Parking brake							
Service brake							
Steering							
Transmission							
Mast lift up/down							
Mast tilt							
Mast side/squeeze							
Other:							
Other:							

**Code: ✓ = OK    X = Deficiency    NA = Not Applicable**

**Emergency Action Plan  
&  
Fire Prevention Plan**

**Framing Authority**  
Independence Village

**EMERGENCY ACTION PLAN**

Events may occur which dictate the evacuation of the facility such as fire, severe inclement weather, power failure, etc.. Additionally events may occur which dictate the need for emergency medical responders. These sets of events fall under our Emergency Action Plan and a multitude of objectives must be met.

The first and foremost objective is the safety of all our personnel. To achieve this level of safety, our plan is designed to get personnel away from danger, treat injury, and provide for a thorough and accurate accounting of all employees.

There may well be situations where certain employees, trained in first aid and/or fire fighting procedures, may prevent a small emergency situation from becoming a major disaster. In these types of situations, these employees, identified in this plan, will remain on the job site to perform the function for which they are trained provided they may perform these duties, in their judgment, in a safe manner. At no time will any employee put himself/herself at risk.

All personnel will receive training on our emergency action plan during initial safety training as well as when our plan changes or the employee's responsibilities change.

If appropriate, on a job site, this emergency action plan will posted with our emergency escape route diagram and emergency telephone numbers.

When working at a client's facility, our personnel will fall under the provisions of their emergency action plan.

All exits will be identified with a sign having the word "EXIT" plainly legible. Exit signs will be suitably illuminated. Doors, passageways, stairs, etc., which appear to be an exit but are not shall be identified by a sign that reads, for example: "Not an Exit".

Aisles and passageways shall be kept clear to provide a direct, easy egress from our facility.

It is important that the actual implementation of this plan be simple, direct, and carried out without confusion. Each employee must know how to alert others, how to call for assistance, the location of fire extinguishers, the escape route, the rendezvous point (and being accounted for so that others do not put themselves at risk looking for a person who has already reached safety), and specific tasks that may be required of specific personnel during emergency procedures.

A copy of 29 CFR 1926.35, Employee Emergency Action Plans is readily available for review in our Safety Program.

The following are standard operating procedures:

### **EMERGENCY MEDICAL RESPONSE**

Should an injury occur that requires an emergency medical responder, the below listed actions will be taken in order given:

1. Call the emergency response number posted adjacent to this plan.
2. Call the Administrative Office at: \_\_\_\_\_.
  - a. Help will immediately be sent and a person will be designated to direct the emergency responders to the injured person.
  - b. If appropriate, Material Safety Data Sheets will be provided the emergency responders.
3. Provide any medical assistance you are trained and certified to do. Do not provide any medical assistance you are not trained to do.

### **ASSIGNED FIRST AID PROVIDERS**

NAME

---

---

---

---

[Note: If none, enter "None".]

**FACILITY EVACUATION PLAN**  
**(FIRE/EXPLOSION/SEVERE WEATHER/MECHANICAL FAILURE, ETC.)**

THE ORDER TO EVACUATE IS GIVEN BY:

\_\_\_\_\_  
(Example: Fire Bell; Three (3) Blasts of an Air Horn; Public Announcement, etc.)

TO ALERT OTHERS:

\_\_\_\_\_  
(Example: Activate alarm; notify main office, Ext No., etc.)

LOCATION OF FIRE EXTINGUISHERS, NEAREST LISTED FIRST:

\_\_\_\_\_  
(Type) (Location)

\_\_\_\_\_  
(Type) (Location)

\_\_\_\_\_  
(Type) (Location)

RENDEZVOUS POINT:

\_\_\_\_\_  
(Example: Parking lot; by dumpster, etc.)

SPECIFIC HAZARDS TO BE AWARE OF:

\_\_\_\_\_  
(Example: List nearby hazardous chemicals. If none, enter "none")

**ROSTER OF PERSONNEL WITH SPECIFIC  
DUTIES DURING AN EVACUATION**

<u>NAME</u>	<u>TITLE</u>	<u>DUTIES</u>
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____

NOTE: Examples of specific duties: Deenergizing certain equipment or machinery; accounting for personnel at rendezvous point; manning fire extinguishers; directing emergency responders; on alert for First Aid delivery; rescue team member; etc. If none, enter: "None".

**Framing Authority**  
Independence Village

**FIRE PREVENTION PLAN**

Reference the Fire Protection and Fire Prevention portions of our Safety Program. This referenced sections deal with procedures to prevent a fire, and, in the event of a fire, the various limitations of fire extinguishers. Further reference our Emergency Action Plan which deals with actions to take in the event of a fire and/or evacuation. This Fire Prevention Plan deals not with handling a fire emergency, but rather preventing a fire in the first place.

**HOUSEKEEPING**

One of the first rules of fire prevention is good housekeeping. Good housekeeping can prevent a fire from starting (improper storage of combustibles, for example) and should there be a fire, good housekeeping can: 1) help prevent the spread of the fire, and 2) make fighting the fire an easier task. Some specific housekeeping rules that impact directly on fire prevention are:

- a. Combustible liquids must be stored and covered in approved containers.
- b. All chemical spills including, of course, combustible liquids, must be cleaned up immediately.

NOTE: Care must be taken when cleaning up chemical spills. Information on appropriate personal protective equipment; proper disposal; proper cleanup procedures; required ventilation, etc. is found on the products Material Safety Data Sheet.

- c. Cleanup materials and damaged containers must be properly disposed.
- d. Combustible liquids and trash must be segregated and stored away from ignition sources.
- e. Aisle ways will be kept free of clutter and trash.
- f. Fire exits will never be blocked.

## **FIRE FIGHTING EQUIPMENT**

One often thinks of fire fighting equipment as it relates to the workplace as fire extinguishers. This is true, yet there are other, often more important, pieces of equipment such as sprinkler systems and outside hydrants. While portable fire extinguishers may prevent a small fire from becoming a major disaster, they are not designed to handle large fires. Below listed are items included in our Fire Prevention Plan:

- a. Approved fire extinguishers will be checked on at least an annual basis and they shall always be charged and ready for use.
- b. Portable fire extinguishers will be mounted, located, and identified for easy accessibility.
- c. Fire hydrants will be kept clear and, during the winter months, not be buried by snow.

### **ELIMINATION OF MAJOR WORKPLACE FIRE HAZARDS**

1. Smoking is allowed only in designated areas and smoking materials will be totally extinguished and placed in the appropriate receptacles.
2. All chemical and chemical products will be handled and stored in accordance with the procedures noted on their individual MSDS.
3. Debris will not be allowed to accumulate on the Job Site.
4. Special precautions will be taken when working with an open flame (such as welding) and those areas will be made fire safe by removing or protecting combustibles from ignition.
5. Equipment installed on heat producing equipment will be regularly and properly maintained to prevent accidental ignition of combustible materials in accordance with manufactures instructions. These instructions are incorporated, by reference, in this Plan

### **TRAINING**

Training in fire protection will be accomplished upon initial assignment and annually thereafter as part of our overall safety program. This training shall include items that deal with employee protection in the event of an emergency. All employees will be apprised of the fire hazards of the materials and processes to which they are exposed.



# Accident Investigation Form

# Framing Authority Independence Village

## ACCIDENT INVESTIGATION FORM

Injured Employee: \_\_\_\_\_ Date: \_\_\_\_\_

Age: \_\_\_\_\_ Job Title: \_\_\_\_\_ Project/Job: \_\_\_\_\_

Date & Time of Accident/Injury: \_\_\_\_\_ Injury: \_\_\_\_\_  
(Date) (Time) (Yes/No)

Nature of Injury or Property Damage: \_\_\_\_\_

Statement of employee involved in the injury or accident (what happened) : \_\_\_\_\_

Witness 1 statement: \_\_\_\_\_

Witness 1 Name & Job Title: \_\_\_\_\_

Witness 2 statement \_\_\_\_\_

Witness 2 Name & Job Title: \_\_\_\_\_

Supervisor/competent person statement \_\_\_\_\_

Was there an injury? \_\_\_\_ Was medical treatment required? \_\_\_\_ Possible lost time accident? \_\_\_\_

Signature of Supervisor/competent person: \_\_\_\_\_

Report Investigated by: \_\_\_\_\_ Date: \_\_\_\_\_

Report review by: \_\_\_\_\_ Date: \_\_\_\_\_

Findings:

Cause of incident: \_\_\_\_\_

Means of preventing a reoccurrence: \_\_\_\_\_

This record will be maintained in the Safety Program Administrator's office for a period of 2 years from the date of accident/injury unless a longer retention is required by law.

If more than 10 employees at any one time in the previous calendar year, this information will be used to complete OSHA Forms 300 and 301 which are used to record and classify occupational injuries and illnesses. Recordable injuries and illnesses must be entered on OSHA Forms 300 and 301 within seven (7) days of receiving information that a recordable injury or illness has occurred.